

SIEMENS

Product data sheet

6GK1901-0DB20-6AA8



[nicht versorgt: PMD_ABS675_001_000]

-
-

IE FC M12 PLUG PRO 2X2 M12 PLUG CONNECTOR
W. RUGGED METAL HOUSING AND FC
CONNECTING METHOD,
WITH AXIAL CABLE OUTLET (D CODED)1
PACKAGE = 8 PIECES FOR SCALANCE X208 PRO
AND ET200 PRO PN

10 Mbit/s
100 Mbit/s

Interfaces

Number of electrical connections

- [nicht versorgt - für Industrial Ethernet FC TP-Leitungen]
- for network components and terminal equipment

4

1

Design of the electrical connection / [nicht versorgt - FastConnect]

Yes

Mechanical data

material / of the housing

metal

Design, dimensions and weight

Width

19 mm

Height

19 mm

Depth

73 mm

Net weight

40 g

Permitted ambient conditions	
Ambient temperature	
• during operating	-40 °C ... 85 °C
• during storage	-40 °C ... 85 °C
• during transport	-40 °C ... 85 °C
Relative humidity / at 25 °C / without condensation / during operating / maximum	95 %
Product properties, functions, components / general	
Product feature / [not supplied - silicon-free]	Yes
Composant produit	
• décharge de traction	Yes
Standards, specifications, approvals	
Verification of suitability	
• RoHS conformity	Yes
• UL-registration	Yes
letzte Änderung:	Nov 21, 2011