




Figure similar

Model	
Product designation	feeder unit for BD01 busbar trunking system
Protection class	
Protection class IP	IP54
Main circuit	
Operating frequency / rated value	
• minimum	50 Hz
• maximum	60 Hz
Operating voltage / at AC	
• at 50 Hz / rated value / maximum	400 V
• at 60 Hz / rated value / minimum	400 V
• at 60 Hz / rated value / maximum	400 V
Operating current	
• for circuit 1 / at AC / at 50 Hz / rated value / maximum	100 A
• for circuit 1 / at AC / at 60 Hz / rated value / maximum	100 A

Connections

Connectable conductor cross-section / in the feeder box

- minimum 6 mm²
- maximum 50 mm²

Mechanical Design

Height	104 mm
Width	150 mm
Length	0.26 mm
Mounting type	ceiling / wall
Material / of the busbar	copper

Declaration of Conformity



EG-Konf.

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=BVP:034259>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/BVP:034259>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=BVP:034259

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>