MA300 Access Control Fingerprint reader(MF)




Overview:

MA300, one of the innovative biometric fingerprint readers for access control applications. Offering unparalleled performances by adopting an advanced ZK fingerprint algorithm for reliability, precision and excellent matching speed. It is metallic casing and IP65 rated which enables it to be resistant from water, dust and other outside damages.

MA300 offers the flexibility to be installed standalone or with any third party panels that support 26-bit wiegand. User can be enrolled by the administrator card when the device works in standalone mode.TCP/IP and RS485 are available, so that the device can be connected easily and conveniently.

Integrated with ACT Enterprise SW Version 2.10 or later. The MA300 is a perfect solution for biometrics working with ACT for internal and external mounting scenarios. Enrollment is simple and easy with the use of the SLK20R reader.





VANDERBILT

MA300 Access Control Fingerprint reader(MF)

MA300 Access Control Fingerprint reader(MF):

Rugged Structure and Extra Durability

IP65 rated waterproof and dustproof structure.

Metallic Casing

Vandal-proof for outdoor installation

Fast and Accurate Fingerprint Algorithm

1 touch a-second user recognition. Store 1,500 templates, 10,000 cards and 100,000 transactions

Easy Installation and Connectivity

Wiegand input & output, Network interface by TCP/IP or RS485

Full Access Control Features

Anti-passback, Access control interface for 3rd party electric lock, door sensor, exit button, alarm and doorbell

Zeasy operation and Management

Fingerprint and RF card reader for multi-model authentication

Integrated with ACT Enterprise

The MA300 is integrated with ACT Enterprise. Fingerprint Templates are captured via the SLK20R USB enrollment reader directly into ACT Enterprise Software and the template is transferred to any MA300 over IP on the same network.

Works with ACT Mifare Classic Cards

The MA300 works with ACT Mifare classic cards reading the secure element of the ACT cards. If using 3rd party Mifare cards, the CSN will be returned via ACT Controllers.



Additional Information :

Enrollment Requirement

- For use with ACT Enterprise Software 1 enrollment reader SLK20R is required
- 1 Enrollment reader is required per system

Access Control Support:

- Biometric Support on ACT Enterprise SW Version 2.10 or later
- License required to work with ACT Enterprise
- Part Number for ACTE-Bio P54508-P123-A100
- ACTE-Bio License is sold as a per door License



MA300 Access Control Fingerprint reader(MF)

Technical Data					
Vanderbilt Material Number	N54504-Z152-A100				
Power Supply	3A/12V DC				
Operating Temperature	-10 °C- 60 °C				
Operating Environment	Internal/External, Surface mounting				
IP Rating	IP65				
Gross Weight	1.15kg				
Dimensions (H x W x D mm)	73 × 148× 34.5				
Material: Body	Stainless Steel				
Communication	RS485,TCP/IP,USB-host				
Wiegand Signal	Input & Output				
ID Card Capacity	10,000				
Transaction Capacity	100,000				
Fingerprint Capacity	1,500 templates				
Sensor	ZK Optical Sensor				
Algorithm Version	ZK Finger v10.0				









Ordering Information:

Туре	Art. No.	Description	Weight*
MA300	N54504-Z152-A100	MA300 Access Control Fingerprint reader(MF)	0.615kg
SLK20R	N54504-Z150-A100	SLK20R USB Silk ID Fingerprint reader	0.160kg
ACTE-Bio	P54508-P123-A100	ACTE-BIO Biometrics Licence	N/A

Other Available Products

Туре	Art. No.	Description	Weight*
SF420	N54504-Z151-A100	SF420 Access Control Fingerprint Reader(MF)	0.402kg

*Gross weight of the product inclusive of the weight of its accessories and packaging.



Vanderbilt International Ltd.

Clonshaugh Business and Technology Park Clonshaugh, Dublin D17 KV 84, Ireland Classical August 2560