

SUPRA-SK



APPLICATION

For extreme use on hand-operated percussion drills and drills up to 1300 watt with mounting thread or conical mount.

TYPE

Impact-resistant and self-tightening flat jaw drill chuck. Also suitable for counterclockwise rotation by radial locking.

CUSTOMER BENEFITS

- Concentricity of up to 0.25 mm
- Increase in the clamping force proportional to the cutting force by automatic retightening function and no releasing in counterclockwise rotation
- Impact-resistant by radial locking for universal use

TECHNICAL FEATURES

- Strong retaining ring
- Hardened and superfinished
- Suitable for counterclockwise rotation up to maximal 15 Nm



A02

SUPRA-SK for hand-operated percussion drills and drills



Item no.	Size	Type	Clamping capacity mm	Mount	Concentricity deviation max. mm	External Ø mm	Length opened mm	Length closed mm	Weight g
249910	10	S	0,5-10	3/8"-24	0,3	40	66	73,7	428
305188	10	S	0,5-10	B 12	0,25	40	68	75,7	416
249804	13	S	1-13	1/2"-20	0,3	42,8	74,2	83,3	537
305221	13	S	1-13	B 12	0,25	42,8	77	86,1	575
305203 ¹⁾	13	S	1-13	B 16	0,25	42,8	80,2	89,3	585

¹⁾ Shortened: B16 by 2.5 mm

