

SUPRA-S



APPLICATION

Suitable for stationary drills and hand-operated drills.

TYPE

Self-tightening flat jaw drill chuck.

CUSTOMER BENEFITS

- ② Concentricity of up to 0.17 mm
- ② Increase in the clamping force proportional to the cutting force by the automatic retightening function
- ② Easy and quick clamping of tools for maximum user-friendliness

TECHNICAL FEATURES

- Strong retaining ring
- All components made from steel
- Hardened and superfinished
- Only suitable for clockwise rotation



A02

SUPRA-S light design mainly for stationary drills and hand-operated drills



Item no.	Size	Type	Clamping capacity mm	Mount	Concentricity deviation max. mm	External Ø mm	Length opened mm	Length closed mm	Weight g
871029	8	S	0-8	3/8"-24	0,25	32	61,5	67,6	285
871038	10	S	0,5-10	3/8"-24	0,25	35,8	66	73,7	370
871039	10	S	0,5-10	1/2"-20	0,25	35,8	66	73,7	377
871049	13	S	1-13	3/8"-24	0,25	40,2	76,3	83,6	610
871050	13	S	1-13	1/2"-20	0,25	40,2	76,3	83,6	548
871046	13	S	1-13	B12	0,17	40,2	78,8	86,1	593
871047 ¹⁾	13	S	1-13	B16	0,17	40,2	82,3	89,6	581
871062	16	S	3-16	1/2"-20	0,25	46	87,5	97,5	880
871063	16	S	3-16	5/8"-16	0,25	46	87,5	97,5	865
871057 ¹⁾	16	S	3-16	B16	0,17	46	88,5	98,5	858
871058 ²⁾	16	S	3-16	B18	0,17	46	92	102	875

¹⁾ Shortened: B16 by 2.5 mm

²⁾ Shortened: B18 by 7 mm

