






Nuts for T-slots (T-nuts)

DIN 508

Nuts for T-slots (T-nuts)

tempered, strength class 10. The nuts for the T groove can only experience a full load when the screw connection exists over the entire length of the thread.



Order no.	D x Slot	A	E	H	K	Packaging Unit	Weight [g]
80002	M 5x 6	5,7	10	8	4	50	4
80010	M 6x 8	7,7	13	10	6	100	9
80028	M 8x10	9,7	15	12	6	100	12
140301	M 8x12*	11,7	18	14	7	50	22
140327	M 8x14*	13,7	22	16	8	50	41
153460	M 8x16*	15,7	25	18	9	25	50
153478	M 8x18*	17,7	28	20	10	25	91
80036	M10x12	11,7	18	14	7	50	22
80234	M10x14*	13,7	22	16	8	50	37
80366	M10x16*	15,7	25	18	9	25	60
81265	M10x18*	17,7	28	20	10	25	87
80044	M12x14	13,7	22	16	8	50	35
80168	M12x16*	15,7	25	18	9	25	50
158907	M12x18*	17,7	28	20	10	25	82
80051	M14x16*	15,7	25	18	9	25	50
80176	M14x18*	17,7	28	20	10	25	70
80069	M16x18	17,7	28	20	10	50	70
80184	M16x20*	19,7	32	24	12	25	110
155630	M16x22*	21,7	35	28	14	25	176
159418	M16x24*	23,7	40	32	16	10	260
159426	M16x28*	27,7	44	36	18	-	383
80077	M18x20*	19,7	32	24	12	25	110
80242	M18x22*	21,7	35	28	14	10	163
80085	M20x22	21,7	35	28	14	25	155
80192	M20x24*	23,7	40	32	16	10	235
158899	M20x28*	27,7	44	36	18	-	355
80093	M22x24*	23,7	40	32	16	10	220
80358	M22x28*	27,7	44	36	18	10	340
80101	M24x28	27,7	44	36	18	-	322
80200	M24x30*	29,7	48	38	19	-	440
80218	M24x36*	35,6	54	44	22	-	700
80119	M27x32*	31,6	50	40	20	-	460
80127	M30x36	35,6	54	44	22	-	590
80226	M30x42*	41,6	65	52	26	-	1150
80135	M36x42	41,6	65	52	26	-	1010
80143	M42x48	47,6	75	60	30	-	1600
80150	M48x54	53,6	85	70	34	-	2300

* AMF works standard.

On request:

Special makes on request.