

Lille hus med forlænget neddrejet spids



APPLICATION

For counter-clamping workpieces on turning and grinding machines.
Especially suited for cramped work area between centre point and workpiece.

TYPE




Compact design with minimum casing diameter.
With extended and profiled centre point.

CUSTOMER BENEFITS

- Enlarged work area and better workpiece accessibility thanks to narrow casing diameter and extended and profiled centre point
- Maximum rigidity at high speeds thanks to compact design
- Maximum concentricity deviation of 0.008 mm for maximum precision

TECHNICAL FEATURES

- Body hardened and ground
- Tip angle 60°



A06

Slim **with small casing diameter** and **profiled and extended centre point**, body hardened and ground - tip angle 60°

Item no.	1241695	1243505	1243507	1243509
Mount MT	2	3	4	5
Size	02	04	08	10
A mm	73	74	88,5	119
B mm	32	34	42	58
D mm	15	15	20	30
G mm	17,78	23,825	31,267	44,399
K mm	29,5	32	37,5	51,5
P mm	6	8	10	12
R mm	12	16	20	26
Workpiece weight max. kg	50	100	150	180
Concentricity deviation max. mm	0,008	0,008	0,008	0,01
Speed max. min⁻¹	7000	7000	6300	4300
Weight approx. g	320	460	1000	2600
Spare live centres	1241758	1241759	1241760	1241761