

Combi 308 IP66/IP67 - 4 mm²

Material	Polypropylene
Material sealing gasket	TPE
Temp. range min	-30 °C
Temp. range max	100 °C
Temperatures during install.	-5 °C - 60 °C
Protection class	IP66 / IP67
Glow wire test	750 °C
Voltage	400 V
Rated current / A (Terminal)	32 A
Rated cross section	4 mm ²
Terminals/poles	5-pole, 4,0 mm ²
Fixing	4 internal openings
Ø cable diameter min	3 mm
Ø cable diameter max	12 mm
External dimensions LxWxH	85 x 85 x 51mm
Type of cable gland	M 20 x 1,5
Tariff number	85369010

Remarks:




IP66: using the membrane entry
IP67: using the threaded entry together with ESKV cable gland

Equipment:

- 8 M20 threaded membrane entries
- 4 captive cover screws
- including mounting clip
- including terminal block 5-poles, 4mm²

Fixing:

With mounting clip or 4 internal openings outside of the sealing area



EL-number	Type	LxBxH	Terminal	Cable Ø	RAL	Packing
1321465158	308	85x85x51	-	3 - 12	7035	100
1321465161	308	85x85x51	-	3 - 12	9001	100
1321465174	308/5	85x85x51	5-poles	3 - 12	7035	100
1321465226	308	85x85x51	-	3 - 12	9005	100
1321465239	308/5	85x85x51	5-poles	3 - 12	9005	100