

Data sheet

Cable tape

Composition: Recycled PE-LD
Colour: Various
Processing: Extrusion
Additive: Colour 2%

3. juli 2023

Side 1 af 1

Typical mechanical properties

Testing	Testing standard	Test condition	Value	Unit
Density	DIN EN ISO 1183	23°C	0,94	g/cm ³
Tensile strength	DIN EN ISO 527	1mm/min	16-18	MPa

Specifications

Purpose of use	Tape for cable protection
Tolerance width	±2,0mm
Tolerance thickness:	
1,00-1,70mm	±0,10mm
1,71-2,00mm	±0,15mm
2,01-3,00mm	±0,20mm
3,01-4,00mm	±0,25mm
>4,01mm	±0,30mm
Recycling rate	100%

Note:

The data listed in this document are based on our current state of knowledge. Specific specifications cannot be guaranteed nor can the suitability for specific applications be deduced from above data. The client is committed to convince himself of the suitability of the product. The data do not release the client from the obligation to sustain a qualified product control.

LETBEK A/S
03-07-2023, Denmark, Product Management.

LETBEK A/S

Hornevej 18
6862 Tistrup
Denmark

CVR: DK-24257134

+45 7529 9444
info@letbek.com

letbek.com

LETBEK sp z o.o.

Ul. Poznańska 165
62-052 Komorniki
Poland

VAT: PL-7792494776

+48 601 841 919
info@letbek.com

letbek.com

