

Product type designation

**SCALANCE M876-4 LTE (EU)**  
SCALANCE M876-4 (EU); FOR WIRELESS IP-COMMUNICATION FROM ETHERNET BASED AUTOMATION DEVICES VIA LTE(4G)-MOBILE RADIO, OPTIMIZED FOR USE IN EUROPA, VPN, FIREWALL, NAT 4-PORT SWITCH 2X SMA ANTENNA, MIMO TECHNOLOGY 1XDIG. INPUT, 1XDIG. OUTPUT PLEASE NOTE NATIONAL APPROVALS!



Transmission rate	
Transfer rate	10 Mbit/s, 100 Mbit/s
Transfer rate	
• for GPRS transmission / with downlink / maximum	85.6 kbit/s
• for GPRS transmission / with uplink / maximum	85.6 kbit/s
• with eGPRS transmission / with downlink / maximum	236.8 kbit/s
• with eGPRS transmission / with uplink / maximum	236.8 kbit/s
• with UMTS transmission / with downlink / maximum	14.4 Mbit/s
• with UMTS transmission / with uplink / maximum	5.76 Mbit/s
• for LTE transmission / with downlink / maximum	100 Mbit/s
• for LTE transmission / with uplink / maximum	50 Mbit/s
Interfaces	
Number of electrical connections	

• for internal network	4
• for external network	2
• for power supply	2
Type of electrical connection	
• for internal network	RJ45 port (10/100 Mbit/s, TP, autocrossover)
• for external network	SMA antenna socket (50 ohms)
• for power supply	Terminal strip

#### Signal-Inputs/outputs

Number of electrical connections	
• for digital input signals	1
• for digital output signals	1
Type of electrical connection	
• for digital input signals	Terminal block
• for digital output signals	Terminal block

#### WAN connection

Type of mobile network / is supported	GSM, UMTS, LTE
Type of mobile wireless service / is supported	GPRS, eGPRS, HSPA+
Operating frequency / for GSM transmission	900 MHz, 1800 MHz
Operating frequency / with UMTS transmission	900 MHz, 1800 MHz, 2100 MHz
Operating frequency / for LTE transmission	800 MHz, 900 MHz, 1800 MHz, 2100 MHz, 2600 MHz

#### Supply voltage, current consumption, power loss

Supply voltage / Rated value	24 V
Supply voltage / rated value	10.8 ... 28.8
Type of voltage / of the supply voltage	DC
Consumed current / at rated supply voltage / maximum	330 mA
Power loss [W]	
• maximum	8 W

#### Permitted ambient conditions

Ambient temperature	
• during operation	-20 ... +60 °C
• during storage	-40 ... +85 °C
Relative humidity / at 25 °C / during operation / maximum	95 %
Protection class IP	IP20

#### Design, dimensions and weight

Design	compact
Depth	127 mm
Height	147 mm
Width	35 mm
Mounting type	

- 35 mm DIN rail mounting
- S7-300 rail mounting
- S7-1500 rail mounting
- wall mounting

Yes  
Yes  
Yes  
Yes

#### Product properties, functions, components / general

##### Product function

- DynDNS client
- no-ip.com client

Yes  
Yes

#### Product functions / management, configuration

##### Product function

- CLI
- web-based management
- MIB support
- TRAPs via email

Yes  
Yes  
Yes  
Yes

##### Protocol / is supported

- Telnet
- HTTP
- HTTPS

Yes  
Yes  
Yes

##### Type of configuration

Web-based management

#### Product functions / Diagnosis

##### Protocol / is supported

- SNMP v1
- SNMP v2
- SNMP v2c
- SNMP v3

Yes  
Yes  
Yes  
Yes

##### Product function

- Statistics Packet Size
- Statistics packet type
- Error statistics
- SysLog
- Packet Filter Log

No  
No  
No  
Yes  
Yes

#### Product functions / DHCP

##### Product function

- DHCP client
- DHCP server - internal network

Yes  
Yes

#### Product functions / Routing

##### Router function

- NAT (IP masquerading)
- Port forwarding
- NAT traversal

Yes  
Yes  
Yes

<ul style="list-style-type: none"> <li>• 1:1 NAT</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• DNS cache</li> </ul>	Yes
<b>Product functions / Security</b>	
Suitability for operation / Virtual Private Network	Yes
Firewall version	Statefull Inspection
Product function	
<ul style="list-style-type: none"> <li>• Password protection</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• packet filter</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Broadcast/Multicast/Unicast Limiter</li> </ul>	No
Product function	
<ul style="list-style-type: none"> <li>• broadcast blocking</li> </ul>	No
<ul style="list-style-type: none"> <li>• with VPN connection</li> </ul>	IPsec, OpenVPN (as Client)
Number of possible connections / with VPN connection	20
Type of authentication / with Virtual Private Network / PSK	Yes
Protocol / is supported	
<ul style="list-style-type: none"> <li>• IPsec tunnel and transport mode</li> </ul>	Yes
Key length	
<ul style="list-style-type: none"> <li>• 1 / with IPsec AES / with Virtual Private Network</li> </ul>	128 bit
<ul style="list-style-type: none"> <li>• 2 / with IPsec AES / with Virtual Private Network</li> </ul>	192 bit
<ul style="list-style-type: none"> <li>• 3 / with IPsec AES / with Virtual Private Network</li> </ul>	256 bit
<ul style="list-style-type: none"> <li>• with IPsec 3DES / with Virtual Private Network</li> </ul>	168 bit
Type of Internet key exchange / with Virtual Private Network	
<ul style="list-style-type: none"> <li>• main mode</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• quick mode</li> </ul>	Yes
Type of packet authentication / with Virtual Private Network	MD5, SHA-1, SHA-256, SHA-384, SHA-512
IETF profile / with Virtual Private Network / X.509v3 certificate	Yes
<b>Product functions / Time</b>	
Protocol / is supported	
<ul style="list-style-type: none"> <li>• NTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• SNTP</li> </ul>	Yes
<b>Standards, specifications, approvals</b>	
Standard	
<ul style="list-style-type: none"> <li>• for EMC</li> </ul>	ETSI EN 301 489-1, ETSI EN 301 489-7, ETSI EN 301 489-24, EN 61000-6-2, EN 61000-6-4

<ul style="list-style-type: none"> <li>• for hazardous zone</li> </ul>	EN 60079-15, EN 60079-0, II 3 G Ex nA IIC T4 Gc, KEMA 07ATEX0145 X
<ul style="list-style-type: none"> <li>• for emitted interference</li> </ul>	ETSI EN 301 489-1, ETSI EN 301 489-7, ETSI EN 301 489-24, EN 61000-6-4
<ul style="list-style-type: none"> <li>• for interference immunity</li> </ul>	ETSI EN 301 489-1, ETSI EN 301 489-7, ETSI EN 301 489-24, EN 61000-6-2
Certificate of suitability	
<ul style="list-style-type: none"> <li>• CE marking</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Railway application in accordance with EN 50121-3-2</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Railway application in accordance with EN 50121-4</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Railway application in accordance with EN 50155</li> </ul>	Yes; no coated printed circuit boards
<ul style="list-style-type: none"> <li>• railway application in accordance with EN 61373</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Fire protection in accordance with EN 45545-2</li> </ul>	Yes
MTBF / at 40 °C	55 y

#### Further Information / Internet Links

Internet-Link	
<ul style="list-style-type: none"> <li>• to website: Selector for cables and connectors</li> </ul>	<a href="http://www.siemens.com/snst">http://www.siemens.com/snst</a>
<ul style="list-style-type: none"> <li>• to website: Selector SIMATIC NET SELECTION TOOL</li> </ul>	<a href="http://www.siemens.com/snst">http://www.siemens.com/snst</a>
<ul style="list-style-type: none"> <li>• to website: Industrial communication</li> </ul>	<a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a>
<ul style="list-style-type: none"> <li>• to website: Industry Mall</li> </ul>	<a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>
<ul style="list-style-type: none"> <li>• to website: Information and Download Center</li> </ul>	<a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a>
<ul style="list-style-type: none"> <li>• to website: Image database</li> </ul>	<a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a>
<ul style="list-style-type: none"> <li>• to website: CAx Download Manager</li> </ul>	<a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>
<ul style="list-style-type: none"> <li>• to website: Industry Online Support</li> </ul>	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>

#### Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

**last modified:**

09/20/2017