

Product name	General Purpose Fuel & Oil hose
	Benzin- & Olieslange – Coder no. NE1060-xxx
Description	Lining : NBR Nitril gummi black smooth / Sort glat Reinforcement : high strength textile yarns/Poyester armering Cover : NBR-PVC, black smooth Sort glat
Lengths	5 mm to 25 mm = 50 mt, 32 mm & 38 mm = 40 mt.
Application	Black industrial-quality Fuel and oil hose for use in all types of industrial the hose are also used for compressed air, fat and mineraloil. Hard-wearing surface that also has excellent weather and ozone resistance
Branding	2 Blue longitudinal stripes with === BP 60 BAR === Embossed with Oil and Fuel 20/60 bar
Temperature	-25°C til 80°C,

Nominal Diameter	Inner Diameter	Outer diameter	A 23° C			Length	Wall thickness	Weight/meter
			Working-pressure	Burst-Pressure	Bending radius			
mm	"	mm	Bar	Bar	mm	mt	mm	g/m
5,0		11,0	20	60		60	3,00	
6,0	1/4"	13,0	20	60		60	3,50	150
8,0	5/16"	15,0	20	60		60	3,50	185
10,0	3/8"	17,0	20	60	-	60	3,50	215
13,0	1/2"	21,0	20	60	-	60	4,00	315
16,0	5/8"	24,0	20	60	-	60	4,00	370
19,0	3/4"	29,0	20	60	-	60	5,00	525
25	1"	35,0	20	60	-	60	5,00	655
32	1-1/4"	43,0	20	60	-	40	5,50	905
38	1-1/2"	50,0	20	60	-	40	6,00	1200

Tolerance on weight : ± 5%

Tolerance on other data: according to ISO 1307

	Firma.MTDK.....
--	-----------------