

Product name	IQ Welding Hose Oxygen Blue
Description	Lining : SBR/EPDM, black Reinforcement : PVA Cover : EPDM, blue
Lengths	50 and 100 MT
Application	Lightweight, flexible, smooth, blue hose for oxygen, to DIN EN 559, ISO 3821. For use with industrial autogenic welding equipment, usually together with red acetylene hose. Also ideal for natural gas and air.
Temperature	-30°C til 80°C,

Nominal Diameter mm	Inner Diameter "	Outer diameter mm	A 23° C			Length mt	Wall thickness mm	Weight/meter g/m
			Working-pressure Bar	Burst-Pressure Bar	Bending radius mm			
5,0	-	12,0	20	60	50	50	7,0	115
6,3	1/4"	13,3	20	60	63	50	7,0	146
8,0	-	14,6	20	60	80	50	6,6	172
10,0	-	17,0	20	60	100	50	7,0	203
12,5	1/2"	19,4	20	60	125	50	6,9	257
20,0	3/4"	28,5	20	60	200	50	8,5	399
32,0	1 1/4"	44,0	10	20	175	50	12,0	775
51,0	2"	65,0	10	20	420	50	14,0	1880

Tolerance on weight : $\pm 5\%$

Tolerance on other data: according to ISO 1307

	Firma.MTDK...08062021
--	-----------------------