



600-PRT1620-177: Henco 5L PE-RT Ø16x2 600m



Commercial information

The Henco 5L PE-RT pipes are made of five layers; a PE-RT inner pipe, an adhesive layer and a centrally positioned oxygen barrier, protected by an outer PE-RT layer. Thanks to the oxygen barrier the pipe responds to the requirements specified in DIN 4726 for oxygen diffusion heating systems. Thus the Henco 5L PE-RT pipes are perfectly suitable for use in heating installations.

Certificates

Applications

Underfloor Heating, Drinking Water, Heating, Cooling, Sanitary

Solutions

Underfloor Heating, Building Installations, Industry, Infra

Technical characteristics

Material	Polyethylene (PE)	Outer pipe diameter	16 Millimetre
Material quality	PE-RT I	Wall thickness	2 Millimetre
Diffusion-proof	✓	Standard Dimension Ratio (SDR)	9
Nominal diameter	DN 12	Max. operating pressure at max. medium temperature	6 Bar
Connection 1	Tube end	Outer diameter mantle pipe	0 Millimetre
Connection 2	Tube end	RAL-number pipe	0
Capped	✗	Number of sealing rings, sleeve	0
Chamfered	✗	Wall roughness	0,00 Millimetre 7
With mantle pipe	✗	Expansion coefficient	0,18 Millimetre per metre Kelvin
Pipe colour	Other	Medium temperature	- Degrees celsius 10 7 0
Flexible	✓	Lambda value	0,41 Watt per meter Kelvin
With thermal insulation	✗	Min. bending radius	80 Millimetre
With heating cable	✗	Min. bending radius without tools	80 Millimetre
UV resistant	✗	Outer diameter thermal insulation	0 Millimetre
SVGW certified	✗	Thickness of thermal insulation	0 Millimetre
Type approval according to BBR/EKS	✗	Water content	0,11 Litre per metre 3

Related products