Besma International Chem a/s

plant established in 1976. We develop, manufacture and sell detergents to the industrial sector and

to minimise the load on both the working environment and the natural environmen



Prior Solvent E

Product information

2023-09-12/JF Copyright©

Product type

- Water-rinsable cold degreaser.
- Oil, tar and wax remover.

What to use the product for?

- Cleaning of oil and grease-contaminated machinery, tools, interiors, floors, etc.
- Removal of adhesive residue from sticky labels.
- Dissolution of rust treatment products, for example stains on textiles.
- Dewaxing of new cars.
- Removal of bitumen.
- Cold degreasing in cleaning tanks/parts washer.

Product advantages

- Effective dissolution of oil, grease, wax and bitumen.
- Can be rinsed off with water.
- Low odour.

Seaning agents based on advanced environmental technology

- Aids fast separation in oil separator.
- Free of aromatics.
- High flash point low evaporation.
- Easily biodegradable.

Working solution

Use undiluted

Water-rinsable cold degreaser. May air dry. Dissolves tar, wax, glue, oil, soot and grease.



How to use the product

- Oil and grease-contaminated parts: Apply with a brush or low-pressure sprayer. Leave to work for about 10 minutes. Rinse with cold or hot water. It is fastest to rinse with hot water.
- Dewaxing:

Apply Prior Solvent E to the wax-protected surfaces. Pour a couple of litres in a bucket and wash with a soft brush or sheepskin wash mitt until the wax layer has loosened completely from the paintwork. Use a pressure washer to rinse with hot water. Can also be rinsed manually with water and a brush.

- Adhesive residue:
 - Dab or spray onto the adhesive. Leave to work for 5-10 minutes until the adhesive has softened. Scrape or wash off.
- Surfaces that may come into contact with foodstuffs must be rinsed thoroughly with clean water.

Technical information

Read the safety data sheet before use.

Tel. +45 7585 7433

MAL-code:

MAL code: (1993)