


E10083XX Color Blank for Nordic Wall Outlets and Panels







For more information please call 1-800-Belden1

See Put-ups and Colors

Description:

Color Blank for Nordic Wall Outlets and Panels, Manufactured in Denmark

SUITABLE APPLICATIONS:

Suitable Applications Color Blank for use in Belden Nordic Wall Outlets and Panels

OUTLET SPECIFICATION:

FACEPLATE:

Material Flame Retardant Plastic UL-94V0, PC-ABS (Acrylonitrile Butadiene Styrene)

Dimensions (H x W x D) 26 x 21 x 9.6 mm

APPLICABLE STANDARDS & ENVIRONMENTAL PROGRAMS:

RoHS Compliant Yes

SUITABILITY:

Suitability - Indoor Yes

FLAME TEST:

UL Flame Test For Material UL-94 V0

PUT-UPS AND COLOR:

Item	Description	Put-Up* (pcs)	Ship Weight(kg)	Color
E1008300	Color Blank, Black	24	0.058	Black
E1008320	Color Blank, Red	24	0.058	Red
E1008340	Color Blank, Yellow	24	0.058	Yellow
E1008350	Color Blank, Green	24	0.058	Green
E1008360	Color Blank, Blue	24	0.058	Blue

Detailed Specifications & Technical Data



E10083XX Color Blank for Nordic Wall Outlets and Panels

E1008380	Color Blank, Grey	24	0.058	Grey
E1008390	Color Blank, White	24	0.058	White

^{*} Packed in a White Cardboard Box.

Revision Number: 1 Revision Date: 01/12/2017

©Copyright 2013 Belden, Inc All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & amp; Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.