



Roxtec R UG™ gennemføring

Tætning i fleksibel konfiguration til flere kabler og rør, der indføres via fundamenter.

Roxtec R UG™ er en gennemføring til flere kabler og rør, der indføres via fundamenter. Tætningen muliggør et mix af små og store kabler og rør i samme åbning og fungerer som langtidsholdbar barriere mod oversvømmelser, gas, fugt og gnavere. Gennemføringen kan modstå ekstrem kabelbøjning og kan installeres i muffer, rør og kerneborede huller også under våde forhold og i miljøer med rindende vand.

- Vandtæt
- Gnaverbestandig
- Pladsbesparende
- Hurtig og nem at montere
- Nem at vedligeholde og inspicere

Byggekonstruktion



Beton og mursten

Monteringstype



Eksisterende åbning

Normeringer og certifikater

Tæthed

- Gas: 0,3 bar (konstant)
- Vand: 0,3 bar (konstant)
- IP 68

Rammedimensioner

mm/kg

De nedenstående rammevarianter udgør et begrænset udvalg. Du kan se hele udvalget af rammer og konfigurationer på [roxtec.com](https://www.roxtec.com).

Title	Pakkeareal	Åbningsmål Ø	Vægt	Art.-nr.
R 100 UG	60 x 60	100 - 102	0.8	156872
R 150 UG	90 x 90	150 - 152	1.9	108693
R 200 UG	120 x 120	200 - 202	3.1	108698

Data om tætningskomponenter

Tætningskomponenter



Lubrikant



RM UG™-modul med Multidiameter™

For mere information, besøg venligst [roxtec.com](https://www.roxtec.com).

Foreslåede tætningskit

mm/kg



Title	Konfiguration	Åbningsmål Ø	Vægt	Art.-nr.
R 150/9 UG	9x (10.0-23.5)		2.8	117821
R 150/6 UG	5x (10.0-23.5), 1x (24.0-52.0)		2.6	120859
R 200/7 UG	3x (24.0-52.0), 4x (10.0-23.5)	200 - 202	4.5	117854
R 100/4 UG	4x (10.0-23.5)		1.2	156874
R 200/15 UG	7x (9.5-31.0), 8x (4.0-13.0)		4.5	117855
R 100/6 UG	1x (4.0-13.0), 4x (4.0-13.0), 1x (9.5-31.0)		1.2	156875
R 200/4 UG	4x (24.0-52.0)		4.5	117822

The product information provided by Roxtec does not release the purchaser of the Roxtec system, or part thereof, from the obligation to independently determine the suitability of the products for the intended process, installation and/or use.

Roxtec gives no guarantee for the Roxtec system or any part thereof and assumes no liability for any loss or damage whatsoever, whether direct, indirect, consequential, loss of profit or otherwise, occurred or caused by the Roxtec systems or installations containing components not manufactured by an authorized manufacturer and/or occurred or caused by the use of the Roxtec system in a manner or for an application other than for which the Roxtec system was designed or intended.

Roxtec expressly excludes any implied warranties of merchantability and fitness for a particular purpose and all other express or implied representations and warranties provided by statute or common law. User determines suitability of the Roxtec system for intended use and assumes all risk and liability in connection therewith. In no event shall Roxtec be liable for indirect, consequential, punitive, special, exemplary or incidental damages or losses.

The Roxtec products are offered and sold in accordance with the conditions of the Roxtec General Terms of Sales. The latest version of the Roxtec General Terms of Sales can be downloaded from <https://www.roxtec.com/en/about-us/about-roxtec/general-terms-of-sales/>

We reserve the right to make changes to the product and technical information without further notice. Any errors in print or entry are no claims for indemnity. The content of this publication is the property of Roxtec International AB and is protected by copyright.

This document was generated on: 2023-10-16