

Technical Data Sheet

Roxtec Lubricant

Internal document ID and revision
ROXNAV-339576052-53/TDS-1106-v.1.0 Rev. 2

Version approval date
2023-09-14



Product description

Roxtec Lubricant is a natural tallow that is used to lubricate the sealing modules, the compression units and the inside of the frames. This simplifies movement in the frame for the sealing modules and ensures correct compression in the seal.

Application instructions

All surfaces must be clean and free from dirt, grease and other contamination before application. Apply a thin film directly on the rubber sealing surfaces, frame or sleeve. Application in radiuses and sharp corners can be done by putting a small amount on the finger and smearing it out.

Environment, health and safety

More detailed information can be found in the relevant Safety Data Sheet.

Product data

Type	Natural tallow
Physical shape	Grease, paste
Color	White
Application temperature	>0°C (Lubricant), the ambient temperature can be colder
Storage	To be stored in dry and dark place in its original container between +5–+30°C. Ten years of storage time when kept cold.
Asbestos free	Yes
Halogen free	Yes
Solvent free	Yes
RoHS compliant	Yes

Disclaimer

The products manufactured by Roxtec International AB are sold in accordance with Roxtec International AB's general conditions of sale and delivery. The information provided does not release you – the receiver of provided information and/or purchaser of these products – from the obligation to determine independently the suitability of these products for the intended processes and/or installations and/or uses.