

Monteringsledninger, PVC-isolerede & varmebestandige

Installation cables, PVC insulated & heat-resistant

Standard: HD 21.7

Standard: HD 21.7



Konstruktion:

Construction:

1 Kobberleder, entrådet kl. 1
Copper conductor, solid, cl. 1

2 Isolation, blyfri PVC, varmebestandig
Insulation, lead-free PVC, heat-resistant

Anvendelse:

Application:

Indre ledninger i brugs- og belysningsgenstande.

Cables to be installed inside electrical devices and lighting components.

Egenskaber:

Properties:

Mærkespænding	300/500 kV
Rated voltage	
Prøvespænding	2 kV AC
Test voltage	
Max. drifttemperatur	90 °C
Max. operating temperature	
Max. kortslutningstemperatur	160 °C
Max. short-circuit temperature	
Min. håndteringstemperatur	5 °C
Min. handling temperature	
Max. lagertemperatur	40 °C
Max. storage temperature	

Brandprøve	IEC 60332-1
Fire test	
Max. tilladeligt træk	50 N/mm ² v/træk i lederen
Max. pulling force	50 N/mm ² on conductors
CE-overensstemmelse	Lavspændingsdirektivet
CE-conformity	Low Voltage Directive
RoHS	Ja
RoHS	Yes
Certificering	HAR
Certificat	

Tekniske data (G):

Technical data (G):

Dimension No. of cores and cross-section	Farve Color	Levering Delivery	Udvendig dimen- sion, nom. Outer diameter, nom.	Udvendig dimen- sion max. Outer diameter max.	Ca. vægt Cable mass approx.	El-nr. Product number	EAN-nr. EAN-nr.
mm ²		m	mm	mm	kg/km		
1X0,75	Hvid White	Sp 100	2,3	2,5	11	30 32 306 054	 5 702950 255473

NKT® er et registreret varemærke ejet af NKT. Ophavsretten i dette dokument tilhører NKT på tidspunktet for udgivelse. Informationen i dokumentet er alene informativ og indeholder således ingen bindende forpligtelser eller erklæringer og ingen garantier.

NKT® is a registered trademark of NKT. © The copyright of this document is vested in NKT. All rights reserved at the time of issuance. This data was prepared for informational purposes only and does not contain any representations, legally binding declarations or guarantees.