



103370

NANOTTICA 1.5ft ES TRS PCc 8000/840 DALI 3F

8596328033704



- Degree of protection: IP66/IP69
- Ambient temperature: -25–45 °C
- Impact strength: IK10
- Life time: 50000 hours
- System efficacy: 171 lm/W
- Colour rendering index CRI: 80-89, 4000–4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- Cable glands: PG 13.5 thread
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 18
- Max. number of luminaires per circuit breaker C16: 30
- Flickering value Pst LM: 1
- Power factor: 0,95
- Stroboscope effect value SVM: 0,4
- Total harmonic distortion: 10
- Energy efficiency class of the light source: C

- Body: clear PC (high mechanical resistance, UV stability)
- Diffuser: clear PC with nano-optics (high mechanical resistance, UV stability)
- Reflector: steel sheet, white (RAL 9003), modified for indirect lighting
- Clips: stainless steel + polyamide
- Sealing: polyurethane (PUR), foam-filled base groove
- Connection: screwless seven-pole terminal block, 7-wire connecting cabling for feed-through installation (1.5 mm2 cross-section, 2.5 mm2 available on demand)
- Absolute control over emitted light thanks to patented nano-optics
- Variable suspension spacing ranging from 970 - 1230 mm; enable the light to be installed onto suspension fittings left over from previous lighting
- Basic beam angle: medium beam (MB); optimal mounting height: 3.5 to 8 m
- Digitally dimmable DALI driver (AC/DC)



Code	Type	Ta Max.: [°C]	Luminous flux of LED modules [lm]	Luminous flux of light fitting: [lm]	Power consumption: [W]	System efficacy: [lm/W]	Net weight: [kg]	A [mm]	D [mm]
103370	NANOTTICA 1.5ft ES TRS PCc 8000/840 DALI 3F	45	8170	7680	44,8	171	2,1	1455	970 - 1230

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES



CERTIFICATION



DOWNLOAD



