



Universal Glue – White

Rapid high performance hot melt glues liquefy when heated and quickly fill gaps and stick to the materials. They cool, harden and reach high bond strength in several seconds. They also allow to move assemblies immediately - open time - to eliminate clamps and reduce drying time – set time - .

Applications :

For a wide range of light-duty to medium-duty applications involving different types of material. The glue works ideally on various material and for all kind of bonding requiring a moderate glue output. Also good for applications where white glue is needed. To be used with EG212, CG270 and BGX300.



Features :

Made of EVA basis.

Solvent free and non irritant.

Universal glue for all kind of bonding. Glue dries quick, helps to cover wider surfaces quickly, prevents from holding the parts too long.

Low viscosity for high flow rate which increase productivity.

Packed in short and long PET blisters of 14 pcs each :

- Short sticks for easier switch to different speciality glues and better handling.
- Long sticks for higher efficiency, less reloading.

Storage :

Unlimited in standard ambient conditions: 15 to 35 °C. Store away from heat. Store in dry, dust-free, and well ventilated environment. Keep in cool and dark area.

Specifications :

- Diameter : 12mm
- Stick length : 190mm / 94mm
- Colour : White
- Softening point (Ring & Ball) : 80 - 96 °C
- Open time : ~ 30 seconds
- Set time : ~ 30 seconds
- Application range : 170 - 190 °C according to the type of applicator and used materials



Description	Packaging	Art. No	EAN	Inner/Outer
Glue D12 Univ. White 14pcs*94mm West	Blister	40107355	3221631073554	10pcs/80pcs
Glue D12 Univ. White 14pcs*94mm East	Blister	5000694	4051661021527	10pcs/80pcs
Glue D12 Univ White 14pcs*190mm	Blister	40107361	3221631073615	10pcs/40pcs

1. All data and recommendations are based on Rapid's research and experience but are provided as recommendations. It is the customer responsibility to validate that the result best meets his needs for a specific application. The customer is the only liable party in case of non Compliance or poor result.
2. The technical data refer to each product specifically and must not be applicable to other Rapid's products or to competitors' products.
3. Rapid's liability is restricted to supply of products according to product specifications.

ISABERG RAPID AB, BOX 115
SE-335 03 HESTRA, SWEDEN
www.rapid.com

Rapid®
SVENSK EFFIXITY