

Chain	Code	Pitch P	Roller diameter d1	Inner width b1	Pin diameter d2	Pin length L	Pin length Lc	Plate height h2	Plate thickness T	Minimum breaking load Qmin	Weight q	Norm DIN / ANSI / ISO	Norm DIN / ANSI / ISO
06B-1	ECO06B-1	9,525	6,350	5,720	3,280	13,150	14,100	8,200	1,300	9,000	0,410	DIN	8187
08B-1	ECO08B-1	12,700	8,510	7,750	4,450	16,700	18,200	11,800	1,600	18,000	0,690	DIN	8187
10B-1	ECO10B-1	15,875	10,160	9,650	5,080	19,500	20,900	14,700	1,700	22,400	0,930	DIN	8187
12B-1	ECO12B-1	19,050	12,070	11,680	5,720	22,500	24,200	16,000	1,850	29,000	1,150	DIN	8187
16B-1	ECO16B-1	25,400	15,880	17,020	8,280	36,100	37,400	21,000	4.15/3.10	60,000	2,710	DIN	8187
20B-1	ECO20B-1	31,750	19,050	19,560	10,190	41,300	45,000	26,400	4.50/3.50	95,000	3,700	DIN	8187
24B-1	ECO24B-1	38,100	25,400	25,400	14,630	53,400	57,800	33,200	6.00/4.80	160,000	7,100	DIN	8187
08B-2	ECO08B-2	12,700	8,510	7,750	4,450	31,000	37,500	11,800	1,600	32,000	1,340	DIN	8187
10B-2	ECO10B-2	15,875	10,160	9,650	5,080	36,100	43,600	14,700	1,700	44,500	1,840	DIN	8187
12B-2	ECO12B-2	19,050	12,070	11,680	5,720	42,000	69,300	16,000	1,850	57,800	2,310	DIN	8187
16B-2	ECO16B-2	25,400	15,880	17,020	8,280	68,000	81,500	21,000	4.15/3.10	106,000	5,420	DIN	8187