

DATASHEET

RJ45-Hirose Connector TM31 black ,100 pcs., 3 Elements,
Cat.6A



General data

Channel Class EA up to 500 MHz (Cat.6A)
For stranded wires (AWG 24/7, AWG 26/7, AWG 27/7)
Shielded version
Core insulation about 0.9 - 1.0 mm
Cable diameter max. 6.6 mm
The set consists of RJ plug, anti-kink sleeve and guide plate
Suitable crimping tool DCW1002 + DCW1002.1 or 39934.2

Allgemeine Daten

Connection type	crimp
Type of connector	RJ45 8(8)
Suitable for litz wire conductor	True
Special tool necessary	True
Suitable for solid core	False
AWG-range for litz wire conductor	24 - 27
Suitable for flat cable	False
Category	6A (TIA)

This datasheet was created automatically on 15-11-2023 . Technical changes reserved.



DATASHEET

RJ45-Hirose Connector TM31 black ,100 pcs., 3 Elements, Cat.6A

Suitable for round cable	True
Model	plug

Elektrische Eigenschaften

screened	True
----------	------

Available variants

ArtNr.	Bezeichnung	Colour
H7642.4-1	RJ45-Hirose Connector TM31 black, 1 pcs., 3 Elements, Cat.6A	black
H7642.4-10	RJ45-Hirose Connector TM31 black, 10 pcs., 3 Elements, Cat.6A	black
H7642.4-50	RJ45-Hirose Connector TM31 black, 50 pcs., 3 Elements, Cat.6A	black
H7642.4-100	RJ45-Hirose Connector TM31 black ,100 pcs., 3 Elements, Cat.6A	black

This datasheet was created automatically on 15-11-2023 . Technical changes reserved.

