









Model	ANT2206		ANT2105	
Product photo				
Space	Indoor		Outdoor	
Frequency band (MHz)	2400 - 2500	4900 - 5875	2400 - 2483	5150 - 5875
Gain	6 dBi	8 dBi	4.5 dBi	7 dBi
VSWR	2.0:1 Max.	2.0:1 Max.	2.0:1 Max.	2.0:1 Max.
Polarization	Linear, vertical		Linear, vertical	
Radiation pattern: H-plane				
Radiation pattern: V-plane				
HPBW/Horizontal	65°		360°	
HPBW/Vertical	75°		30°	
Front to back ratio	12 dB		-	
Impedance	50 Ω		50 Ω	
Connector	RP-SMA plug		N type plug	
Survival wind speed	-		216 km/hr	
Temperature	-10°C to 55°C/14°F to 131°F		-10°C to 70°C/14°F to 158°F	
Humidity	95% at 55°C (131°F)		95% at 55°C (131°F)	
Radome color	White, black		White	
Radome material	ABS, UV resistant		ABS	
Dimensions (WxDxH)(mm/in.)	76 x 86 x 118/2.99 x 3.39 x 4.65		f 22 x 183	
Weight (g/lb.)	110/0.24		70/0.15	
Accessory kit	- Screw kit - Quick installation guide		-	