

Dual-wall Heat Shrink Tubing / Flexible / Flame retardant / 3:1/Adhesive lined

Features:

- Crosslinked co-extruded adhesive lined Polyolefin •
Shrink ratio: 3:1
- Flame retardant • Excellent sealing and insulation properties •
UV resistant

Approvals:

- UL224 125 °C VW-1 600 V • Meets: RoHS
- Meets: SAE-AMS-DTL-23053/4

Application:

- Operating temperature: -55 °C to +125 °C • Minimum
shrink temperature: +70 °C
- Minimum full recovery temperature: +110 °C • Longitudinal
change: 0 ± 10% max.



For electronic, automotive and consumer
goods. Waterproofing, electrical
insulation/protection.
Free from harmful substances such as
PBB's, PBBO's, PBBE's.

Type / Size	As supplied: Inside diameter in mm (min.)	After recovery: Inside diameter in mm (max.)	After recovery: Wall thickness in mm (+/- 0,05)	Reel / Meter
7800315009 - 3/1 BLACK	3	1	1	2,5
7800315006 - 6/2 BLACK	6	2	1	3
7800315003 - 9/3 BLACK	9	3	1,4	3
7800315001 - 12/4 BLACK	12	4	1,6	2,5
7800315002 - 19/6 BLACK	19	6	2,15	2
7800315005 - 24/8 BLACK	24	8	2,4	1,5