

Article No. : 1FK2205-2AF01-0MB0

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :



Figure similar

| Basic motor data        |                                                           |
|-------------------------|-----------------------------------------------------------|
| Motor type              | Permanent-magnet synchronous motor, Natural cooling, IP65 |
| Motor type              | Compact                                                   |
| Static torque           | 3.60 Nm                                                   |
| Static current          | 2.9 A                                                     |
| Maximum torque          | 10.80 Nm                                                  |
| Maximum current         | 9.5 A                                                     |
| Maximum speed           | 6,000 rpm                                                 |
| Rotor moment of inertia | 3.1500 kgcm <sup>2</sup>                                  |
| Weight                  | 3.8 kg                                                    |

| Rated data                      |           |
|---------------------------------|-----------|
| SINAMICS S120, BLM/SLM 3AC 400V |           |
| Rated speed                     | 3,000 rpm |
| Rated torque                    | 3.00 Nm   |
| Rated current                   | 2.5 A     |
| Rated power                     | 0.94 kW   |

| Encoder system |                                                             |
|----------------|-------------------------------------------------------------|
| Encoder system | Encoder AM22DQC: Absolute encoder 22 bit + 12 bit multiturn |

| Motor connection |                                  |
|------------------|----------------------------------|
| Connection type  | Double cable connection for S120 |
| Connector size   | M17                              |

| Mechanical data               |                                            |
|-------------------------------|--------------------------------------------|
| Design acc. to Code I         | IM B5 (IM V1, IM V3)                       |
| Vibration severity grade      | Grade A                                    |
| Shaft height                  | 48                                         |
| Flange size (AB)              | 95 mm                                      |
| Centering ring (N)            | 80 mm                                      |
| Hole circle (M)               | 100 mm                                     |
| Screw-on hole (S)             | 6.5 mm                                     |
| Overall length (LB)           | 145 mm                                     |
| Diameter of shaft (D)         | 19 mm                                      |
| Length of shaft (E)           | 40 mm                                      |
| Length of flange diagonal (P) | 120 mm                                     |
| Shaft end                     | Plain shaft                                |
| Color of the housing          | Standard (Anthracite, similar to RAL 7016) |

