

Article No. : 1FK2306-4AC01-0SB0

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :



Figure similar

Basic motor data	
Motor type	Permanent-magnet synchronous motor, Natural cooling, IP65
Motor type	High Inertia
Static torque	12.00 Nm
Static current	4.5 A
Maximum torque	38.00 Nm
Maximum current	17.0 A
Maximum speed	3,300 rpm
Rotor moment of inertia	29.8000 kgcm ²
Weight	11.4 kg

Rated data	
SINAMICS S120, BLM/SLM 3AC 400V	
Rated speed	2,000 rpm
Rated torque	10.50 Nm
Rated current	4.1 A
Rated power	2.20 kW

Encoder system	
Encoder system	Encoder AS22DQC: Absolute encoder single turn 22 bit

Motor connection	
Connection type	Double cable connection for S120
Connector size	M23

Mechanical data	
Design acc. to Code I	IM B5 (IM V1, IM V3)
Vibration severity grade	Grade A
Shaft height	63
Flange size (AB)	125 mm
Centering ring (N)	110 mm
Hole circle (M)	130 mm
Screw-on hole (S)	9.0 mm
Overall length (LB)	244 mm
Diameter of shaft (D)	24 mm
Length of shaft (E)	50 mm
Length of flange diagonal (P)	158 mm
Shaft end	Plain shaft

