

Article No. : 1FK2306-4AC11-0MB0

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :



Figure similar


| Basic motor data | |
|-------------------------|---|
| Motor type | Permanent-magnet synchronous motor, Natural cooling, IP65 |
| Motor type | High Inertia |
| Static torque | 12.00 Nm |
| Static current | 4.5 A |
| Maximum torque | 38.00 Nm |
| Maximum current | 17.0 A |
| Maximum speed | 3,300 rpm |
| Rotor moment of inertia | 30.8000 kgcm ² |
| Weight | 12.8 kg |

| Rated data | |
|---------------------------------|-----------|
| SINAMICS S120, BLM/SLM 3AC 400V | |
| Rated speed | 2,000 rpm |
| Rated torque | 10.50 Nm |
| Rated current | 4.1 A |
| Rated power | 2.20 kW |

| Encoder system | |
|----------------|---|
| Encoder system | Encoder AM22DQC: Absolute encoder 22 bit + 12 bit multiturn |

| Motor connection | |
|------------------|----------------------------------|
| Connection type | Double cable connection for S120 |
| Connector size | M23 |

| Mechanical data | |
|-------------------------------|--|
| Design acc. to Code I | IM B5 (IM V1, IM V3) |
| Vibration severity grade | Grade A |
| Shaft height | 63 |
| Flange size (AB) | 125 mm |
| Centering ring (N) | 110 mm |
| Hole circle (M) | 130 mm |
| Screw-on hole (S) | 9.0 mm |
| Overall length (LB) | 281 mm |
| Diameter of shaft (D) | 24 mm |
| Length of shaft (E) | 50 mm |
| Length of flange diagonal (P) | 158 mm |
| Shaft end | Plain shaft |
| Color of the housing | Standard (Anthracite, similar to RAL 7016) |



| Holding brake | |
|---|-----------|
| Holding torque | 13.00 Nm |
| Average dynamic torque | 6.50 Nm |
| Opening time | 100 ms |
| Closing time | 50 ms |
| Maximum single switching energy ¹⁾ | 1,550 J |
| Service life, operating energy | 774,000 J |
| Rated current ²⁾ | 0.7 A |

¹⁾Up to three consecutive emergency stops and up to 25% of all emergency stops as a Wmax high energy stop possible.
²⁾Typical value for 20°C ambient temperature. At -15°C the break-induced currents can be increased by up to 30%.