

## MOTIP Tar & Resin Remover

Ord.-no.: 000765

### Technical Information



Remove tar, bitumen, asphalt and resin from your car with MOTIP Tar & Resin Remover. Tar & Resin Remover is easy to apply and pH-neutral.

#### Quality & properties

- Leaves no residue
- Excellent dissolving properties
- Misty spray pattern
- User-friendly
- 360° valve

#### Physical & chemical data

- Base: Aliphatic hydrocarbons with alcohol
- Colourname: transparent
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 3500/20 bar
- Storage stability: 10 y
- Content: 600 ML

#### How to use

- Before use, carefully read the directions on the packaging and act accordingly. Not suitable for long-term use on 1K lacquers.
- The aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol.
- Apply the Tar & Resin Remover and allow to take effect.
- Then remove the dirt with a cloth.
- With persistent contamination, repeat the treatment.

#### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

#### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

#### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +31 (0) 561 69 44 00 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

**As of August 17, 2022** – This release replaces all eventually earlier issued versions.