

Battery for Crane Remote Control
GAF-S592MB

Models

Scanreco® 590, 960,
Maxi, Mini, HMF,
Fassi, Palfinger, Effer

Compatibility
Battery Model: 592

Physical Characteristics
Dimension: 50.0 X 29.2 X 149.8 mm (1.97 X 1.15 X 5.90 inch)

Weight: 260 g (9.17 oz.)

Plastic Material: ABS

Electrical Characteristics
Chemistry: Ni-MH

Voltage: 7.2V

Capacity: Typical: 2050mAh; Minimum: 1950mAh

Cell: Gold Peak ReCyko GP210AAHCB

Operation Specification
Charging Voltage: 8.4 ~ 11.4 V

Charging Current: 0.2 ~ 2.0C

Discharging Current: 0.2 ~ 2.0C

Discharging End Voltage: 6.0 V

User Environment
Charging Temperature: $\pm 0 \sim +40^{\circ}\text{C}$ ($+32 \sim +104^{\circ}\text{F}$)

Discharging Temperature: $-20 \sim +50^{\circ}\text{C}$ ($-4 \sim +122^{\circ}\text{F}$)

Storage Temperature: $-20 \sim +50^{\circ}\text{C}$ ($-4 \sim +122^{\circ}\text{F}$)

Prolonged Storage Temp.: $-20 \sim +30^{\circ}\text{C}$ ($-4 \sim +86^{\circ}\text{F}$)

Brand names are registered trademark of their respective owners

Onwell Communication Limited

www.onwellpower.com
sales@onwell.com