

Product type designation

CP 5612
COMMUNICATIONSPROCESSOR CP 5612 PCI-CARD FOR
CONNECTING A PG OR PC WITH PCI-BUS TO PROFIBUS OR
MPI CAN BE USED WITH 32BIT AND 64BIT OPERATING
SYSTEMS ALSO SEE ARTICLE-ID 22611503



Transmission rate	
Transfer rate	
• at the 1st interface / acc. to PROFIBUS	9.6 kbit/s ... 12 Mbit/s
Interfaces	
Number of electrical connections	
• at the 1st interface / acc. to PROFIBUS	1
Design of the electrical connection	
• at the 1st interface / acc. to PROFIBUS	9-pin Sub-D socket (RS 485)
Supply voltage, current consumption, power loss	
Type of voltage / of the supply voltage	DC
Supply voltage	
• 1 / from backplane bus	3.3 V
• 2 / from backplane bus	12 V
Relative symmetrical tolerance / for DC	
• at 3.3 V	9 %
• at 12 V	8 %
Consumed current	
• 1 / from backplane bus / for DC / maximum	0.15 A

• 2 / from backplane bus / for DC / maximum	0.25 A
Active power loss	3.5 W

Permitted ambient conditions

Ambient temperature	
• during operation	5 ... 55 °C
• during storage	-20 ... +60 °C
• during transport	-20 ... +60 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP00

Design, dimensions and weight

Module format	PCI
Width	18 mm
Height	107 mm
Depth	125 mm
Net weight	98 g
Number of plug-in cards of same design / plug-in / per PC station	1
Number of units / Note	-

Performance data

Performance data / open communication

Software / for open communication / by means of SEND/RECEIVE / required	Yes, SOFTNET-PB DP / SOFTNET-PB DP Slave / SOFTNET-PB S7
Number of possible connections / for open communication / by means of SEND/RECEIVE / maximum	50

Performance data / PROFIBUS DP

Software / for DP master function / required	Yes, SOFTNET-PB DP
Service / as DP master	
• DPV0	Yes
• DPV1	Yes
• DPV2	No
Number of DP slaves / on DP master / usable	64
Amount of data	
• of the address area of the inputs / as DP master / total	14640 byte
• of the address area of the outputs / as DP master / total	14640 byte
• of the address area of the inputs / per DP slave	244 byte
• of the address area of the outputs / per DP slave	244 byte
• of the address area of the diagnostic data / per DP slave	244 byte

Software / for DP slave function / required	Yes, SOFTNET-PB DP slave
Service / as DP slave	
• DPV0	Yes
• DPV1	No
Amount of data	
• of the address area of the inputs / as DP slave / total	122 byte
• of the address area of the outputs / as DP slave / total	122 byte
Performance data / S7 communication	
Software / for S7 communication / required	Yes, SOFTNET-PB S7
Number of possible connections / for S7/PG communication / maximum	8
Performance data / multi-protocol mode	
Number of configurable connections / per PC station	207
Product functions / Diagnosis	
Product function	
• Port diagnostics	Yes
Standards, specifications, approvals	
Standard	
• for EMC	89/336/EEC
• for safety / from CSA and UL	CAN/CSA C22.2 & UL 60950-1, UL 1950
• for emitted interference	EN 61000-6-3
• for interference immunity	EN 61000-6-2
Certificate of suitability	
• CE marking	Yes
• C-Tick	Yes
Accessories	
accessories	optional: MPI cable
last modified:	01.12.2014