



MIG svejsseslange - effektiv, hvor pladsen er trang

Model ML 250 TWIST

Standard modeller

LM nr.

4347000015	3 m	0,8	80197250
4347000488	4 m	0,8	80197251
4347000489	5 m	0,8	80197253

Modeller med regulering

4347000474	R 3 m	0,8	80196250
4347000475	R 4 m	0,8	80196251
4347000476	R 3 m	1,0 Alu	80196252



Gasdyse

4347000354	57 mm	80140601*
------------	-------	-----------



4347000353	57 mm	80140600
------------	-------	----------



Kontakttdyse

E-Cu

4347000340	Ø0,6 M6	Ø8x28 mm	80130201
4347000341	Ø0,8 M6	Ø8x28 mm	80130202*
4347000342	Ø1,0 M6	Ø8x28 mm	80130203
4347000343	Ø1,2 M6	Ø8x28 mm	80130204



CuCrZr

4347000348	Ø1,6 M6	Ø8x28 mm	80131204
------------	---------	----------	----------

Dysestok

4347000313	35 mm	80110602 *
4347000312	37 mm	80110601




Holdefjeder

4347000250		80100600
------------	--	----------



Stålliner

4347000404	Hvid	for 0,6-0,8 tråd	80160520
4347000405	Blå	for 0,8-1,0 tråd	80160521*
4347000406	Rød	for 1,2-1,6 tråd	80160522



4,4 m (bruges også til 3 m slanger)

* = Standard monteret ved levering

Alle modeller leveres med spring pin.