
SIEMENS

Product data sheet BVP:261737

BD2C-3-800-SB-1 STANDARD LENGTH 1,25M 800A, N + PE, 4 TAP OFFS



Similar to image

General technical details:		
product designation		trunking unit for BD2 busbar trunking system
Product-type designation		BD2C-3-800-SB-1
Operating current		
• for circuit 1 / at 50 Hz / for AC / rated value / maximum	Α	800
• for circuit 1 / at 60 Hz / for AC / rated value / maximum	Α	800
Resistance against the impulse current / at 690 V / rated value	kA	84
Short-time current resistance (lcw) / at 690 V		
• limited to 1 s / rated value	kA	32
• limited to 0.1 s / rated value	kA	40
Operating frequency / rated value		
• minimum	Hz	50
• maximum	Hz	60
Operating voltage		
• at 50 Hz / at AC / rated value / maximum	V	690
• at 60 Hz / at AC / rated value / maximum	V	690
Insulation voltage		
• for AC / rated value	V	690
• for DC / rated value	V	800

Number of conductors		5		
• without PE		4		
Product component / fire sealing		No		
Mechanical design:				
Conductor cross section / of the (PE)N	mm²	280		
Type of mounting		ceiling / wall		
Width	mm	167		
Height	mm	126		
Color		light grey		
Busbar:				
Configuration of the busbars		L1,L2,L3,N		
Material / of the busbar		copper		
Busway section:				
Length / of the busbar box	m	1.25		
mounting position / of the busbar box		horizontal edgewise, horizontal flat, vertical		
Number of circuits / in one busbar box		1		
Outgoing openings:				
Outgoing point distance	m	0.5		
Number of the outgoing points / maximum		4		
Arrangement of the outgoing points		on both sides		
Ambient conditions:				
Protection class IP		IP52		
Further information:				
Information- and Downloadcenter (Catalogs, Brochures,) http://www.siemens.com/lowvoltage/catalogs				
Global Industry Mall (Online ordering system) http://www.siemens.com/lowvoltage/mall				
Service&Support (Manuals, Certificates, Characteristics, FAQs,) http://support.automation.siemens.com/WW/view/en/BVP:261737/all				
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams,) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=BVP:261737				

last change: Jun 2, 2012