

## Data sheet for SIMOTICS S-1FK2



Figure similar

### MLFB-Ordering data

1FK2205-2AF10-0MA0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Basic motor data		Mechanical data	
Motor type	Permanent-magnet synchronous motor, Natural cooling, IP64	Design acc. to Code I	IM B5 (IM V1, IM V3)
Motor type	Compact	Vibration severity grade	Grade A
Static torque	3.60 Nm	Shaft height	48
Static current	2.9 A	Flange size (AB)	95 mm
Maximum torque	10.80 Nm	Centering ring (N)	80 mm
Maximum current	9.5 A	Hole circle (M)	100 mm
Maximum speed	6000 rpm	Screw-on hole (S)	6.5 mm
Rotor moment of inertia	4.050 kgcm <sup>2</sup>	Overall length (LB)	188 mm
Weight	4.8 kg	Diameter of shaft (D)	19 mm
		Length of shaft (E)	40 mm
		Length of flange diagonal (P)	120 mm
		Shaft extension	Plain shaft

### Rated data

SINAMICS S210, 3AC 400V

Rated speed	3000 rpm
Rated torque	3.00 Nm
Rated current	2.5 A
Rated power	0.94 kW

### Encoder system

Encoder system	Encoder AM22DQC: Absolute encoder 22 bit + 12 bit multiturn
----------------	-------------------------------------------------------------

### Motor connection

Connection type	OCC for S210
Connector size	M17




Figure similar

1FK2205-2AF10-0MA0

Break-induced current for 500 ms <sup>2)</sup>	1.1 A
------------------------------------------------	-------

<sup>2)</sup> Typical value for 20°C ambient temperature. At -15°C the break-induced currents can be increased by up to 30%.