

SRC3-U5A1C1BD000



NOVUX™ Specialty Range Closure 100, splice only, no adapters, no splitters, 24 splices, SMOUV® 45mm splice protectors, black, 2x NVX-CR-SA-SM-NN cable retention

- Modern drop solution offering providers the agility and flexibility to use it in last-mile fiber network applications, both above and below ground
- Protected from harsh conditions by CommScope's Octopus gel sealing technology
- Agnostic to connectivity technologies: splice, connector, field-installable connector for agility and flexibility
- Identification plate for either QR code or customer logo
- QR code and CommScope cTrak® app for one-click access to all product information

Product Classification

Regional Availability	Asia EMEA Latin America North America
Product Type	Single-ended, rectangular fiber closure
Product Brand	NOVUX™
Product Series	SRC100

General Specifications

Cable Capacity, Drop	4 Flat 8.0 x 4.5 mm (0.30 x 0.17 in) 4 Round 1.2–8.0 mm (0.05–0.31 in)
Cable Ports Quantity, total	4 multi-out ports (8 cables)
Cable Sealing Type	Gel filled
Cable Termination Attachments, quantity	2
Closure Sealing Type	Hinged with latch
Closure Style	Single-ended
Color	Black
Mounting	Handhole Partially buried Pedestal Wall/Pole Mount, mounting kit included
Network Area Type	Drop
Port Type	No adapter
Splicing Capacity, maximum	24
Splicing Capacity, Single Fusion, maximum	24
Splicing Type, Supported	Single fusion

Dimensions

SRC3-U5A1C1BD000

Height	267 mm 10.512 in
Width	117 mm 4.606 in
Depth	49 mm 1.929 in
Cable Entry Drop Port Diameter	8 mm 0.315 in

Ordering Tree

SRC

-

U

A

1

C

1

B

D

0

0

0

0

Size and color

1	50 Black
2	50 Gray
3	100 Black
4	100 Gray

Sealing

U	Underground, IP68
---	-------------------

Connector type*

1	SC/UPC
2	LC/UPC
3	SC/APC
4	LC/APC
5	Splice only

*All connector types are grade B

Number of adapters

A	None
K	1
B	2

Cable retention

* See complete details at the bottom of the page.

Splice protector type

A	SMOUV 30
B	SMOUV 45
C	ANT

Splitters

1	None
2	1:2
3	1:4

Number of splices

A	6
B	12
C	24
E	48

Number of pigtails

1	None
A	1
2	2
B	3
3	4

* Cable retention^a

A	None
B	NVX-CR-MC-FT-NN
C	NVX-CR-MC-RD-NN
D	NVX-CR-SA-SM-NN
E	NVX-CR-TI-SM-NN
F	NVX-CR-DU-SL-NN

^a 2 cable attachments are supplied.

Cable Termination Unit (CTU) options

<div><div>B</div><div></div><div>NVX-CR-MC-FT-NN</div><ul style="list-style-type: none">Flat cableMetal clipRange 3 x 5 to 4 x 8 mm</div> <td><div><div>C</div><div></div><div>NVX-CR-MC-RD-NN</div><ul style="list-style-type: none">Round cableMetal clipRange 4 to 6.2 mm</div><td><div><div>D</div><div></div><div>NVX-CR-SA-SM-NN</div><ul style="list-style-type: none">Round cableDia up to 8 mmStrength memberAramid yarnsSingle layer</div><td><div><div>E</div><div></div><div>NVX-CR-TI-SM-NN</div><ul style="list-style-type: none">Round cableDia up to 8 mmAramid yarnsSingle layer</div><td><div><div>F</div><div></div><div>NVX-CR-DU-SL-NN</div><ul style="list-style-type: none">Round cableDia up to 6.2 mmAramid yarnsDual layerCompact length</div></td></td></td></td>	<div><div>C</div><div></div><div>NVX-CR-MC-RD-NN</div><ul style="list-style-type: none">Round cableMetal clipRange 4 to 6.2 mm</div> <td><div><div>D</div><div></div><div>NVX-CR-SA-SM-NN</div><ul style="list-style-type: none">Round cableDia up to 8 mmStrength memberAramid yarnsSingle layer</div><td><div><div>E</div><div></div><div>NVX-CR-TI-SM-NN</div><ul style="list-style-type: none">Round cableDia up to 8 mmAramid yarnsSingle layer</div><td><div><div>F</div><div></div><div>NVX-CR-DU-SL-NN</div><ul style="list-style-type: none">Round cableDia up to 6.2 mmAramid yarnsDual layerCompact length</div></td></td></td>	<div><div>D</div><div></div><div>NVX-CR-SA-SM-NN</div><ul style="list-style-type: none">Round cableDia up to 8 mmStrength memberAramid yarnsSingle layer</div> <td><div><div>E</div><div></div><div>NVX-CR-TI-SM-NN</div><ul style="list-style-type: none">Round cableDia up to 8 mmAramid yarnsSingle layer</div><td><div><div>F</div><div></div><div>NVX-CR-DU-SL-NN</div><ul style="list-style-type: none">Round cableDia up to 6.2 mmAramid yarnsDual layerCompact length</div></td></td>	<div><div>E</div><div></div><div>NVX-CR-TI-SM-NN</div><ul style="list-style-type: none">Round cableDia up to 8 mmAramid yarnsSingle layer</div> <td><div><div>F</div><div></div><div>NVX-CR-DU-SL-NN</div><ul style="list-style-type: none">Round cableDia up to 6.2 mmAramid yarnsDual layerCompact length</div></td>	<div><div>F</div><div></div><div>NVX-CR-DU-SL-NN</div><ul style="list-style-type: none">Round cableDia up to 6.2 mmAramid yarnsDual layerCompact length</div>
---	---	--	---	---

Material Specifications

Material Type	Impact-resistant polymer
---------------	--------------------------

Optical Specifications

Fiber Type	G.657.A1 G.657.A2 G.657.B3
------------	--------------------------------

Page 2 of 3

©2022 CommScope, Inc. All rights reserved. All trademarks identified by ® or ™ are registered trademarks, respectively, of CommScope. All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: January 18, 2022

COMMScope®

SRC3-U5A1C1BD000

Environmental Specifications

Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Environmental Space	Above ground Below ground
Qualification Standards	IEC 60529, IP68 + 2 m waterhead IEC 61753-1, category G
UV Resistance	UV stabilized
Water Resistance	Flash test valve at 2 psi (20 kPa)

Packaging and Weights

Packaging quantity	10
Packaging Type	Box Carton

Included Products

NVX-CR-SA-SM-NN	–	NOVUX™ Cable Termination Unit (CTU) for round cables up to 8 mm diameter, with strength member, aramide yarns, single layer
-----------------	---	---