
SIEMENS

Product data sheet BVP:261892

BD2C-400-TV JUNCTION UNIT T UNIT FRONTSIDE 160-400A



Similar to image

| General technical details: | | |
|---|----|---|
| product designation | | T unit (junction unit) for BD2 busbar trunking system |
| Product-type designation | | BD2C-400-TV |
| Operating current | | |
| • for circuit 1 / at 50 Hz / for AC / rated value / maximum | Α | 400 |
| • for circuit 1 / at 60 Hz / for AC / rated value / maximum | Α | 400 |
| Resistance against the impulse current / at 690 V / rated value | kA | 40 |
| Short-time current resistance (lcw) / at 690 V | | |
| • limited to 1 s / rated value | kA | 16 |
| • limited to 0.1 s / rated value | kA | 20 |
| Operating frequency / rated value | | |
| • minimum | Hz | 50 |
| • maximum | Hz | 60 |
| Operating voltage | | |
| • at 50 Hz / at AC / rated value / maximum | V | 690 |
| • at 60 Hz / at AC / rated value / maximum | V | 690 |
| Insulation voltage | | |
| • for AC / rated value | V | 690 |
| • for DC / rated value | V | 800 |

| | _ | | | |
|---|-----|----------------|--|--|
| Number of conductors | | 5 | | |
| Number of conductors / without PE | | 4 | | |
| Fire resistance class / for fire sealing | | Nein | | |
| Product component / fire sealing | | No | | |
| Mechanical design: | | | | |
| Conductor cross section / of the (PE)N | mm² | 146 | | |
| Type of mounting | | ceiling / wall | | |
| Width | mm | 184 | | |
| Height | mm | 360 | | |
| Color | | light grey | | |
| Busbar: | | | | |
| Configuration of the busbars | | L1,L2,L3,L3,N | | |
| Material / of the busbar | | copper | | |
| Busway section: | | | | |
| Design of the busbar box junction unit / flexible | | No | | |
| Length of the X-dimension / of the busbar box junction unit | | | | |
| • minimum | m | 0.36 | | |
| • maximum | m | 0.36 | | |
| Length of the Y-dimension / of the busbar box junction unit | | | | |
| • minimum | m | 0.36 | | |
| • maximum | m | 0.36 | | |
| Ambient conditions: | | | | |
| Protection class IP | | IP52 | | |
| Further information: | | | | |
| Information- and Downloadcenter (Catalogs, Brochures,) http://www.siemens.com/lowvoltage/catalogs | | | | |

Global Industry Mall (Online ordering system)

http://www.siemens.com/lowvoltage/mall

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

http://support.automation.siemens.com/WW/view/en/BVP:261892/all

 $Image\ database\ (product\ images,\ 2D\ dimension\ drawings,\ 3D\ models,\ device\ circuit\ diagrams,\ ...)$

 $\underline{\text{http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=BVP:261892}$

last change: Apr 26, 2012