





Certifikat

Ordre Nr. 50250 Lemvigh-Müller
Produktions Nr. 2016-50
Vare beskrivelse Klasse 8 4-part kædesling 4,25T 4,0mtr. m/Opkorter kroge og Øje
WLL (Max belastning) Sikkerhedskroge
4,25 Ton
WLL ved 45° 4,25 Ton
WLL ved 60° 3,15 Ton
Produktionsdato 22. Marts 2016
Lovpligtigt eftersyn senest 21. Marts 2017

Anhugning						
Kæde dim				WLL. KG.		
7mm	1500	1200	2120	1500	3150	2240
8mm	2000	1600	2800	2000	4250	3000
10mm	3115	2500	4250	3150	6700	4750
13mm	5300	4250	7500	5300	11200	8000
16mm	8000	6400	11200	8000	17000	11800
Faktor	1	0,8	1,4	1	2,1	1,5

Bemærkninger

Anførte WLL fordrer lige/symmetrisk løft.

Ved ulige/asymmetrisk belastede kædeparter, skal beregnes 0,5 x WLL

Ved tvivlspørgsmål kontakt venligst vor salgsafdeling

Michlar ApS Bekræfter at produktet er fremstillet i henhold til og overholder arbejdstilsynets normer.

For Michlar

