

V250

Light weight crimping head for Cu-terminals 10-800 mm²
and Al-terminals 16-630 mm²


V250




V250 crimp head is to be used together with foot-pump P4000 or pump PS710 (230VAC/24VDC).

Important characteristic:


- weight of only 4,6 kg
- 250 kN crimping force
- using same crimping dies (B-dies, matrix and punches) as in the 1300-system, 2500-system and 1400-system
- working pressure 63 Mpa (630 bar)
- with protection cap
- dimensions Ø111 mm x 280 mm
- crimping range of: Cu-terminals 10-800 mm²
Al-terminals 16-630 mm²
Cu branch connectors (C-sleeves) up to 300 mm²



Die holder V2508,
B-dies, die holder V2506.



Die holder V2508, BC-dies,
die holder V2506.



Die holder V2508,
BNP-dies, die holder V2506.



Die pair 2542
use without dieholders

Storage box LV250

Carry box which takes the tool V250 and all necessary accessories to crimp Elpress Cu terminals and through connectors

Particulars:

- steel reinforced plywood
- Polyethylen insert material
- the box can be used as storage or be taken to site
- sturdy, form cut inserts
- weight 5.2 kg, excl. accessories
- length 570 mm, width 467 mm, height 130 mm

