



Figure similar

Ordering data

6SL3210-5BB13-7UV1

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data		General tech. specifications	
Input		Power factor λ	0.72
Number of phases	1 AC	Offset factor $\cos \varphi$	0.95
Line voltage	200 ... 240 V -15 % +10 %	Efficiency η	0.98
Line frequency	47 ... 63 Hz	Ambient conditions	
Output		Cooling	convection cooling
Number of phases	3 AC	Installation altitude	1000 m (3281 ft)
Rated voltage	400 V	Ambient temperature	
Rated power (HO)	0.37 kW / 0.50 hp	Operation	-10 ... 60 °C (14 ... 140 °F)
Rated power (LO)	0.37 kW / 0.37 hp	Storage	-40 ... 70 °C (-40 ... 158 °F)
Rated current (HO)	2.30 A	Relative humidity	
Rated current (LO)	2.30 A	Max. operation	95 %
Pulse frequency		Communication	
Pulse frequency	8 kHz	Communication	USS, Modbus RTU
Output frequency	0 ... 550 Hz	Standards	
		Compliance with standards	CE, cULus, C-Tick (RCM), KC
		CE marking	EN 61800-5-1 /EN 60204-1 and EN 61800-3

Overload capability

Low Overload (LO)

110 % rated output current for 60 s, cycle time 300 s

High Overload (HO)

150 % rated output current for 60 s, cycle time 300 s



Generated Tue Jul 05 15:49:12 CEST 2016