SIEMENS

Data sheet	6GK5907-4PA00

Product type designation	KEY-PLUG W740 iFeatures
Product description	Swap medium for activating iFeatures for SCALANCE W in Client Mode and for simple device replacement in the event of a fault KEY-PLUG W740, REPLACEABLE MEDIUM FOR ACTIVATING OF IFEATURES FOR SCALANCE W IN CLIENT MODE AND FOR EASY REPLACEMENT OF DEVICE IN CASE OF FAILURE AND FOR STORAGE OF CONFIGURATION DATA.

Suitability for use	Activation of iPCF Client Mode, iPCF-MC Client Mode

Permitted ambient conditions

Ambient temperature	
• during operation	0 ... 60 °C
• during storage	-40 ... +80 °C
• during transport	-40 ... +80 °C
Relative humidity	
• at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

Design, dimensions and weight

Width	24.3 mm
Height	17 mm
Depth	8.1 mm
Net weight	5 g
design of the removable storage	

• C-PLUG	No
• KEY-PLUG	Yes

Product properties, functions, components / general

Storage capacity	256 Mibyte

Further Information / Internet Links

Internet-Link

• to website: TIA Selection Tool	http://www.siemens.com/tia-selection-tool
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to the website: IWLAN	http://www.siemens.com/iwlan
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

last modified: 08/10/2016