



Model	GD-F023T-D	GD-F028T-D	GD-F031T-D	GD-F032T-D	GD-F033T-D	GD-F034T-D	GD-F035T-D	GD-F036T-D
Lamp type	led flood light	led flood light	led flood light	led flood light	led flood light	led flood light	led flood light	led flood light
Lamp Power	15W	30W	50W	80W	120W	200W	300W	400W
Input Voltage(V)	AC180-240V	AC180-240V	AC180-240V	AC180-240V	AC180-240V	AC180-240V	AC180-240V	AC180-240V
Lamp Luminous Flux(lm)	2000 LM	4200LM	7500LM	12000LM	18000LM	30000LM	45000LM	60000LM
CRI(RA)	>80	>80	>80	>80	>80	>80	>80	>80
Color temperature(CCT)	3000K/4000K/6000K	3000K/4000K/6000K	3000K/4000K/6000K	3000K/4000K/6000K	3000K/4000K/6000K	3000K/4000K/6000K	3000K/4000K/6000K	3000K/4000K/6000K
Lamp viewing angle(°)	30°/60°/90°/120 °	30°/60°/90°/120 °	30°/60°/90°/120 °	30°/60°/90°/120 °	30°/60°/90°/120 °	30°/60°/90°/120 °	30°/60°/90°/120 °	30°/60°/90°/120 °
Luminous Efficiency(lm/w)	140-150lm /w	140-150lm /w	140-150lm /w	140-150lm /w	140-150lm /w	140-150lm /w	140-150lm /w	140-150lm /w
Chip Parameter								
LED Quantity	16 pcs	32pcs	48 pcs	96 pcs	160 pcs	240pcs	320 pcs	512pcs
LED Type	3030 SMD	3030 SMD	3030 SMD	3030 SMD	3030 SMD	3030 SMD	3030 SMD	3030 SMD
Chip brand	SAN'AN	SAN'AN	SAN'AN	SAN'AN	SAN'AN	SAN'AN	SAN'AN	SAN'AN
Driver Parameter								
Driver Type	Constant Current driver (CCT) (Own design)							
Power Factor	>0.9	>0.9	>0.9	>0.9	>0.9	>0.9	>0.9	>0.9
Flicker	NO	NO	NO	NO	NO	NO	NO	NO
Surge	4KV	4KV	4KV	4KV	4KV	4KV	4KV	4KV
Basic Parameter								
Working Lifetime(Hours)	≥30000	≥30000	≥30000	≥30000	≥30000	≥30000	≥30000	≥30000
Working temperature(°C)	-25 to +45	-25 to +45	-25 to +45	-25 to +45	-25 to +45	-25 to +45	-25 to +45	-25 to +45
Lamp Body Material	Die-casting aluminum	Die-casting aluminum	Die-casting aluminum	Die-casting aluminum	Die-casting aluminum	Die-casting aluminum	Die-casting aluminum	Die-casting aluminum
Housing finished color	black	black	black	black	black	black	black	black
IP Rating	66	66	66	66	66	66	66	66
cable	50cm	50cm	50cm	50cm	50cm	50cm	50cm	50cm
Delivery time	30 days	30 days	30 days	30 days	30 days	30 days	30 days	30 days
Warranty	5years	5years	5years	5years	5years	5years	5years	5years
MOQ	300 pcs	300 pcs	300 pcs	300 pcs	300 pcs	300 pcs	300 pcs	300 pcs
Dimension	182*122*47mm	242*169*51 mm	282*204*52 mm	337*269*52mm	394*394*56mm	445*392*56mm	497*392*56 mm	503*545*64 mm