

KATLA BL

Aluminium

Aluminium carrier for good thermal management

IK08

Co-extruded polycarbonate housing

Quick connection

Due to clippable end caps and PRACHT SLIDER

HOUSING Co-extruded polycarbonate, impact resistant, IK08.

SEALS Extremely short, ageing resistant silicone seals.

ELECTRICAL COMPONENTS High power LED, LED converter.

THROUGH-WIRING Including 3x1,5 mm² wiring ex works.

ASSEMBLY Variable mounting distances with PRACHT-CLIP-SYSTEM. Suitable for ceiling and rail mounting.

FIELDS OF APPLICATION Parking garages, basements, workshops, 1:1 fluorescent light exchange.

CONFIGURABILITY Possible in the KATLA PRO LINE. E.g.: light colors, control module, emergency lighting modules, REMADE and a lot more.

Individual luminaire, color temperature 4000 K, Ra>80, IP65

Power	Light distribution	Luminous flux	P/N	Length	Weight
1x23 W	120° wide	2800 lm	5231004	1240 mm	1,1 kg
1x45 W	120° wide	5400 lm	5231014	1240 mm	1,1 kg
1x31 W	120° wide	3800 lm	5231005	1540 mm	1,2 kg
1x54 W	120° wide	6500 lm	5231015	1540 mm	1,2 kg



Protection class I according to EN 60598

Protection type IP65

AC/DC 220-240 V 50/60 Hz

PRACHT®

Sealed

Extremely short silicone seals

Incl. Wiring

Factory-made 3x1.5mm²
through-wiring

Variable

PRACHT-CLIP-SYSTEM
for variable mounting

MULTITALENT

**PRICE / PERFORMANCE SLIM
SOLID PROFILE LIGHT
EASY INSTALLATION HOMOGENEOUS LIGHT
1:1 REPLACEMENT ENEC**

3

YEAR
WARRANTY



50.000 h
LIFETIME

IP65



INCL. TW
(3x1,5MM²)



**FROM -20°C
TO +35°C**

PRACHT.COM

+49 64 66 / 91 40-0