



FROST PROTECTED EMERGENCY SAFETY SHOWER
WITH ADDITIONAL EYEBATH / FACEWASH FOUNTAIN.
HEATING ELEMENT AND MODULES ARE REMOVABLE
WITH STANDPIPE IN SITU.
MINIMUM WORKING TEMPERATURE: -35°C

BROEN-LAB

BROEN-LAB A/S
Drejervænget 2, DK-5610 Assens,
T: +45 6376 6376 F: +45 6471 2476
-E: lab@broen-lab.com W: broen-lab.com

	NAME	DATE	DEBUR AND BREAK SHARP EDGES
DRAWN:	S.W.	30/10/12	DIMENSIONS ARE IN MILLIMETRES UNLESS SPECIFIED OTHERWISE
CHECKED:	A.L.	31/10/12	
APPROVED:	A.L.	31/10/12	TOLERANCES: LINEAR: ANGULAR:
MATERIAL:	GALVANISED MILD STEEL		SCALE:1:20
			DO NOT SCALE OFF DRAWING

TITLE:
OUTDOOR EMERGENCY SAFETY SHOWER WITH EYEBATH / FACEWASH FOUNTAIN.
SUITABLE FOR FLAMEPROOF AREAS. SUPPLY VOLTAGE 230V, 50 OR 60 HZ.

FINISH: CLEAN	SHEET 1 OF 1	DWG NO. H7410011000341
------------------	--------------	---------------------------

REVISION

A

A3