

Product type designation

RCoax Antenna ANT792-4DN

IWLAN RCOAX N-CONNECT FEMALE ANTENNA ANT792-4DN
2.4GHZ HELIX ANTENNA,CIRCULAR POLARIZATION
CLOCKWISE; ANTENNA FOR RCOAX SYSTEMS ANTENNA
AMPLIFYING AT 2.4GHZ 4DBI; IP67; AMBIENT TEMPERATURE -
40 UP TO +70 DEGR C



Electrical data

Impedance	50 Ω
Polarization	circular, clockwise
Radiation characteristic	directional
Antenna gain compared to spherical radiator	
• of the WLAN antenna / in the 2.4 GHz frequency band	4 dB
Standing wave ratio (VSWR) / maximum	1.8
Beam angle of antenna	
• in the 2.4 GHz frequency band / horizontal	90°
Number of electrical connections / of the antenna	1
Design of the electrical connection / of the antenna	N-Connector
Design of plug-in connection	female
Angle of inclination / downward / maximum	0°
Front-to-back ratio	2.5 dB
Transmit power / maximum	1 W

Mechanical data

Material	
• of outer shell	Polycarbonate

Permitted ambient conditions

Ambient temperature	
• during operation	-40 ... +70 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C

Protection class IP	IP65
Design, dimensions and weight	
Height	78.7 mm
Diameter	30 mm
Net weight	114 g
Product properties, functions, components / general	
Product property / silicon-free	Yes
Standards, specifications, approvals	
Wireless approval	Current national approvals can be found on the Internet under www.siemens.com/funkzulassungen
Further Information / Internet Links	
Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Information and Download Center	http://www.siemens.com/automation/net/catalog
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	http://support.automation.siemens.com
last modified:	26.01.2015