

Product-type designation

SCALANCE W748-1 M12



IWLAN CLIENT, SCALANCE W748-1 M12,
FOR USE OUTSIDE OF USA, 1 RADIO,
3 N-CON. ANT.CONNECT.,
IEEE 802.11A/B/G/H/N, 2.4/5GHZ,
BRUTTO 450 MBIT/S PRO RADIO,
1 X M12 (MAX. 1 GBIT/S), POE, 24VDC,
IP65 (-20-+60 GRD C), POE,
WPA2/802.11I/E,
PLEASE NOTE NATIONAL APPROVALS! SCOPE OF
SUPPLY: MANUALS ON CD ROM GERMAN/ENGLISH.

Transmission rate

Transmission rate

- | | |
|----------------------------|--------------------|
| • with W-LAN / maximum | 450 Mbit/s |
| • with Industrial Ethernet | 10 ... 1000 Mbit/s |

Interfaces

Number of electrical connections

- | | |
|---|---|
| • for network components and terminal equipment | 1 |
| • for power supply | 1 |
| • for redundant power supply | 1 |

Design of the electrical connection

- | | |
|--------------------|---------------------------------|
| • for power supply | M12 interface (4-pole, A-coded) |
|--------------------|---------------------------------|

design of the removable storage / C-PLUG

Yes

Interfaces / wireless

Number of radio cards / permanently installed

1

Number of electrical connections / for external antenna(s)

3

Design of the electrical connection / for external antenna(s)

N-Connect (socket)

Product property / external antenna can be mounted directly on device

Yes

Supply voltage, current consumption, power loss

Type of / supply voltage

DC

Supply voltage	
• 1 / from M12 Power Connector (A-coded) for redundant power supply	19.2 V
• 2 / from M12 Power Connector (A-coded) for redundant power supply	28.8 V
• from Power-over-Ethernet according IEEE802.3at for type 1 and IEEE802.3af	48 V
• from Power-over-Ethernet according IEEE802.3at for type 2	50 V
Current consumed	
• at 24 V / with DC / typical	0.45 A
• with Power-over-Ethernet according to IEEE802.3at for type 1 and IEEE802.3af / typical	0.22 A
• with Power-over-Ethernet according to IEEE802.3at for type 2 / typical	0.21 A
Active power loss	
• at 24V / for DC / typical	10.7 W
• with Power-over-Ethernet according to IEEE802.3at for type 1 and IEEE802.3af / typical	10.7 W
• with Power-over-Ethernet according to IEEE802.3at for type 2 / typical	10.7 W
Permitted ambient conditions	
Ambient temperature	
• during operating	-20 ... +60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
Relative humidity / at 25 °C / without condensation / during operating / maximum	100 %
Protection class IP	IP65
Ambient condition / for (standard) operation mode	When used under hazardous conditions (Zone 2), the SCALANCE W788-xPRO/RR or W74x-1PRO/RR product must be installed in an enclosure. To comply with EN 50021, this enclosure must meet the requirements of at least IP 54 in compliance with EN 60529.
Design, dimensions and weight	
Width / of enclosure / without antenna	200 mm
Height / of enclosure / without antenna	176 mm
Depth / of enclosure / without antenna	79 mm
Net weight	1.7 kg
Mounting type	
• S7-300 rail mounting	Yes
• wall mounting	Yes
Mounting type	S7-300 rail mounting
Wireless frequencies	
Radio frequency	

• for WLAN in 2.4 GHz frequency band	2.41 ... 2.48 GHz
• for WLAN in 5 GHz frequency band	4.9 ... 5.8 GHz
Product properties, functions, components / general	
Product function	
• Access Point Mode	No
• Client Mode	Yes
Product function	
• Dual Client	No
• iPCF client	Yes
• iPCF-MC client	No
Number of iPCF-capable radio modules	1
Product functions / management, configuration	
Number of manageable IP addresses / in client	8
Product function	
• CLI	Yes
• web-based management	Yes
• MIB support	Yes
• TRAPs via email	Yes
• Configuration with STEP 7	No
• configuration with STEP 7 in the TIA Portal	No
• forced roaming with IWLAN	No
• WDS	No
Protocol / is supported	
• Address Resolution Protocol (ARP)	Yes
• ICMP	Yes
• Telnet	Yes
• HTTP	Yes
• HTTPS	Yes
• TFTP	Yes
• SNMP v1	Yes
• SNMP v2	Yes
• SNMP v3	Yes
• DCP	Yes
• LLDP	Yes
Identification & maintenance function	
• I&M0 - device-specific information	Yes
• I&M1 – higher level designation/location designation	Yes
Product functions / Diagnosis	
Product function	

• PROFINET IO diagnosis	No
• Link Check	No
• connection monitoring IP-Alive	No
• SysLog	Yes
Product functions / VLAN	
Product function / function VLAN with IWLAN	No
Product functions / DHCP	
Product function	
• DHCP client	Yes
• in Client Mode / DHCP server via LAN	No
Product functions / Security	
Product function	
• Management security, ACL-IP based	Yes
• IEEE 802.1x (radius)	Yes
• NAT/NAPT	No
• access protection according to IEEE802.11i	Yes
• WPA/WPA2	Yes
• TKIP/AES	Yes
Protocol / is supported / SSH	Yes
Product functions / Time	
Protocol / is supported	
• SNTP	Yes
• SIMATIC Time	Yes
Standards, specifications, approvals	
Standard	
• for hazardous zone	EN 60079-15:2005, EN 60079-0:2006, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X
• for safety / of CSA and UL	UL 60950-1 CSA C22.2 No. 60950-1
• for hazardous area / of CSA and UL	-
Verification of suitability	
• CE mark	Yes
• EC declaration of conformity	Yes
• C-Tick	Yes
• Railway application in accordance with EN 50155	No
• E1 approval	No
• NEMA4X	No
• Power-over-Ethernet according IEEE802.3at for type 1 and IEEE802.3af	Yes
• Power-over-Ethernet according to IEEE802.3at for type 2	Yes
Standard for wireless communication	

- IEEE 802.11a
- IEEE 802.11b
- IEEE 802.11e
- IEEE 802.11g
- IEEE 802.11h
- IEEE 802.11i
- IEEE 802.11n

Wireless approval

Yes

Yes

Yes

Yes

Yes

Yes

Yes

You will find the current list of countries at:
www.siemens.de/funkzulassungen

Accessories

Accessories

-

letzte Änderung:

Mar 31, 2014