

Product-type designation

MM992-2CU

SCALANCE X ACCESSORY,
MEDIA MODULE MM992-2CU,
2 X 10/100/1000MBIT/S RJ45-PORTS,
ELECTRICAL;
WITHOUT SLEEVE



Interfaces

Number of electrical/optical connections / for network components or terminal equipment / maximum	2
Number of 10/100/1000 Mbit/s RJ45 ports	2
Design of electrical connection	
• for network components and terminal equipment	RJ45 port

Permitted ambient conditions

Ambient temperature	
• during operating	-40 ... +70 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
Relative humidity / at 25 °C / without condensation / during operating / maximum	95 %
Protection class IP	IP20

Design, dimensions and weight

Width	60 mm
Height	22 mm
Depth	100 mm
Net weight	0.08 kg
Type of mounting	

• Installation in media module slot	Yes
Type of mounting	Latched
Standards, specifications, approvals	
Standard	
• for EMC / from FM	FM3611: Class 1, Division 2, Group A, B, C, D / T4, Class 1, Zone 2, Group IIC, T4
• for hazardous zone	EN 60079-0: 2006, EN60079-15: 2005, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X
• for safety / of CSA and UL	UL 60950-1, CSA C22.2 No. 60950-1
• for hazardous area / of CSA and UL	UL 1604 and UL 2279-15 (Hazardous Location), CSA C22.2 No. 213 -M1987, Class 1 / Division 2 / Group A, B, C, D / T4, Class 1 / Zone 2 / Group IIC / T4
• for emitted interference	EN 61000-6-4:2007 (Class A)
• for interference immunity	EN 61000-6-2:2005
Verification of suitability	EN 61000-6-2:2005, EN 61000-6-4:2007
• CE mark	Yes
• C-Tick	Yes
• KC approval	Yes
letzte Änderung:	Sep 30, 2013