

Data sheet for SIMOTICS S-1FK2



Figure similar

MLFB-Ordering data

1FK2210-3AC01-0SA0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Basic motor data		Mechanical data	
Motor type	Permanent-magnet synchronous motor, Natural cooling, IP65	Design acc. to Code I	IM B5 (IM V1, IM V3)
Motor type	Compact	Vibration severity grade	Grade A
Static torque	30.00 Nm	Shaft height	100
Static current	15.0 A	Flange size (AB)	192 mm
Maximum torque	90.00 Nm	Centering ring (N)	180 mm
Maximum current	55.0 A	Hole circle (M)	215 mm
Maximum speed	4400 rpm	Screw-on hole (S)	14.0 mm
Rotor moment of inertia	88.800 kgcm ²	Overall length (LB)	198 mm
Weight	22.0 kg	Diameter of shaft (D)	38 mm
		Length of shaft (E)	80 mm
		Length of flange diagonal (P)	244 mm
		Shaft extension	Plain shaft

Rated data

SINAMICS S210, 3AC 400V

Rated speed	2000 rpm
Rated torque	26.00 Nm
Rated current	13.5 A
Rated power	5.50 kW

Encoder system

Encoder system	Encoder AS22DQC: Absolute encoder single turn 22 bit
----------------	--

Motor connection

Connection type	OCC for S210
Connector size	M23




Figure similar