

# R32 REFRIGERANT SERIES

Suit for R32, 1234yf refrigerant



• Chinese patent



Integrated body structure



Horizontal position easy for reading



Enclosed switch



## Dual Stage

| Model           |                  | V-i125Y-R32    | V-i240Y-R32           | V-i260Y-R32           | V-i280Y-R32           |
|-----------------|------------------|----------------|-----------------------|-----------------------|-----------------------|
| Flow Rate       | 50Hz             | 2.5 CFM        | 3.5 CFM               | 5.0 CFM               | 7.0 CFM               |
|                 |                  | 70 L/min       | 100 L/min             | 142 L/min             | 198 L/min             |
|                 | 60Hz             | 3.0 CFM        | 4.0 CFM               | 6.0 CFM               | 8.0 CFM               |
|                 |                  | 84 L/min       | 113 L/min             | 170 L/min             | 226 L/min             |
| Ultimate Vacuum | Partial Pressure | 2 Pa           | 2x10 <sup>-1</sup> Pa | 2x10 <sup>-1</sup> Pa | 2x10 <sup>-1</sup> Pa |
|                 | Total Pressure   | 150micron      | 15micron              | 15 micron             | 15 micron             |
| Power           |                  | 1/4 HP         | 1/2 HP                | 3/4 HP                | 1 HP                  |
| Inlet Port      |                  | 1/4" Flare     | 1/4" Flare            | 1/4" Flare            | 1/4" Flare            |
| Oil Capacity    |                  | 250 ml         | 325 ml                | 460 ml                | 500 ml                |
| Dimensions      |                  | 290x124x235 mm | 338x138x248 mm        | 395x145x270 mm        | 395x145x270mm         |
| Weight          |                  | 7.2 Kg         | 11.0 Kg               | 16.6 Kg               | 17.0 Kg               |



• Chinese patent



Smaller, lighter, and more convenient  
Suite for R32, 1234yf refrigerant

|                  |                       |
|------------------|-----------------------|
| Model            | V-i2120               |
| Flow Rate        | 12 CFM                |
| Partial Pressure | 2x10 <sup>-1</sup> Pa |
| Total Pressure   | 15 micron             |
| Power            | 1 HP                  |
| Inlet Port       | 1/4" & 3/8" Flare     |
| Oil Capacity     | 500 ml                |
| Dimensions       | 345x135x280 mm        |
| Weight           | 11.5 Kg               |