

H07V2-K (RK 90°C) 450/750 V CPR

Kontakter

Industri
Tlf.: + 45 75 69 33 99
industry-pc.dk@nexans.com

The cable is intended to be used for inside couplings in switch cabinet boxes and similar applications.

BESKRIVELSE

H07V2-K is a lead free, PVC insulated, connecting cable with one circular, multi stranded copper conductor. The cable is designed according to EN 50525-2-31. The conductor has resistance according to EN 60228 class 5. The insulation is marked "NEXANS GS H07V2-K 0,75 SEMKO (HAR) E. H07V2-K meets the requirements for CPR class E.

Certification

Certificeret af INTERTEK SEMKO.

Quality system

Certificeret ifølge ISO 9001, IRIS, ISO/TS 16949 og ISO 14001.



STANDARDER

International EN 50525-2-31



Halogenfri
Nej



Mærkespænding U_o/U
450 / 750 V



Drifttemp.
0 .. 90 °C

Alle tegninger, mønstre, specifikationer, planer og oplysninger om vægt, størrelse og dimensioner i det tekniske eller kommercielle dokumentation fra Nexans er kun vejledende og er ikke bindende for Nexans.

Version 1.0 Genereret 09-11-17 www.nexans.dk Side 1 / 2

 Nexans

H07V2-K (RK 90°C) 450/750 V CPR

Kontakter

Industri
Tlf.: + 45 75 69 33 99
industry-pc.dk@nexans.com

TEKNISKE DATA

Konstruktion

Lederens materiale	Kobber
Isolation	PVC
Halogenfri	Nej

Elektriske egenskaber

Mærkespænding Uo/U	450 / 750 V
--------------------	-------------

Håndteringsinformation

Drifttemperatur	0 .. 90 °C
-----------------	------------

SALGS OG LEVERINGSINFORMATIONER

H07V2-K is delivered in specified lengths. The package is marked with manufacturer, type of cable, length and manufacturing date. On the label on boxes upon request also the customer item number and/or order number.