

Keystone Snap-in-Jack Faceplate Module Datasheet

head office
brand-rex limited
viewfield industrial estate
glenrothes, fife
KY6 2RS
tel: +44 (0) 1592 772124
fax: +44 (0) 1592 775315
web: www.brand-rex.com



Description

Dual Snap-In-Jack Faceplate Module



Features and Benefits

- ◆ Suitable for Brand-Rex approved Snap-in-Jacks both screened and unscreened.
- ◆ Jacks located within metal mounting frame.
- ◆ Cover colour white RAL 9010.
- ◆ Ports protected with hinged door dust caps.
- ◆ Port identification label compartment.
- ◆ Optional earthing point within the metal mounting frame.
- ◆ Design improves cable bending in trunking systems for secure performance.

Part Numbers

Description	Catalogue Number	Colour	Quantity per Pack
Keystone Snap-In-Jack Faceplate Module.	MMCANGDK2453	White RAL 9010	1
Snap in Jack Blank	MMCJAKBLK2	Black	20
Snap in Jack Blank	MMCJAKBLK3	White	20
Faceplate	18985JW	White RAL 9010	10
Double Faceplate	27661AP	White RAL 9010	10

The information contained in this document is valid and correct at the time of issue. However, we reserve the right to modify details without notice in the light of subsequent Standard / Specification changes and ongoing technical developments

Keystone Snap-in-Jack Faceplate Module Datasheet

head office
brand-rex limited
viewfield industrial estate
glenrothes, fife
KY6 2RS
tel: +44 (0) 1592 772124
fax: +44 (0) 1592 775315
web: www.brand-rex.com



Brand-Rex

Packaging

- Each Snap in Faceplate Module (metal mounting frame and central housing) packaged together in cardboard box, qty 5 per box (Snap in jack blanks and faceplates supplied separately)

Applications

- Installation of Snap-In-Jacks for Datacom and Network Installations in poles, floor boxes and wall trunking systems.

Installation

- Suitable for approved Brand-Rex Snap in Jacks, see compatible parts list below.

Description		Catalogue Number	Colour	Quantity per Pack
10GPlus Shielded Snap-in-Jack -	Cable Ready	AC6JAKS000CR	-	12
Cat6 Plus Shielded Snap-in-Jack -	Cable Ready	C6CJAKS000CR	-	12
10GPlus Shielded Snap-in-Jack -	Tool-Free	AC6JAKS000	-	12
Cat6 Plus Shielded Snap-in-Jack -	Tool-Free	C6CJAKS000	-	12
10GPlus Unshielded Snap-in-Jack -	Tool-Free	AC6JAKU002	Black	12
Cat6 Plus Unshielded Snap-in-Jack -	Tool-Free	C6CJAKU002	Black	12
GIGA Plus Unshielded Snap-in-Jack -	Tool-Free	GPCJAKU002	Black	12
GIGA Plus Unshielded Snap-in-Jack -	Lead frame	GPCJAKU013LF	White	50

Mechanical Specifications

Material Data

- Metal Frame: Zinc Alloy
- Central Housing: ABS-FR

Dimensions

- Jack Mounting Angle = 60 Degrees
- Mounting pitch = 60mm x 60mm
- Central housing = 50mm x 50mm

