

TECHNICAL DATA SHEET



PRODUCT NAME

blackbolt® Rust loosener

PRODUCT NUMBER

3356985005

PRODUCT DESCRIPTION

Rust loosener has penetrating additives that, together with graphite, make the product very suitable for loosening rusted-in screws, bolts, valves, machine parts etc. The temperature range is from minus 10° to plus 430°C.

PROPERTIES

High penetration properties

Quick-working

Lubricates and protects

Reduces friction and wear

DIRECTIONS FOR USE

Spray Rust loosener on the article that is to be treated. Let the product work for several minutes before dismantling. The graphite content ensures effective lubrication and sliding properties even at high temperatures and pressures.

MARKINGS/SAFETY

Pressurised container: May burst if heated. Repeated exposure may cause skin dryness or cracking. If medical advice is needed, have product container or label at hand. Read label before use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Pressurized container: Do not pierce or burn, even after use. 38 mass percent of this product is flammable. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. **Keep out of reach of children.**

Warning!

PR number	2105595
Net	370 g.
Volumen	500 ml.
Propellant	Carbon dioxide

Shelf life	Three years from date of manufacture. The product can be used for up to six years after the date of production, provided there is sufficient spray pressure to allow it to be applied to the surface in a satisfactory manner.
------------	--